



circuit breaker 3VA1 IEC Frame 160 breaking capacity class S  $I_{cu}=36\text{ kA}$  @ 415 V  
4-pole, line protection TM210, FTFM,  $I_n=16\text{ A}$  overload protection  $I_r=16\text{ A}$   
permanently set short-circuit protection  $I_i=20 \times I_n$  N conductor unprotected nut  
keeper kit

| Model                                                                                                 |                             |
|-------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                    | SENTRON                     |
| product designation                                                                                   | Molded case circuit breaker |
| design of the product                                                                                 | Line protection             |
| design of the overcurrent release                                                                     | TM210                       |
| protection function of the overcurrent release                                                        | LI                          |
| number of poles                                                                                       | 4                           |
| General technical data                                                                                |                             |
| insulation voltage / rated value                                                                      | 800 V                       |
| operating voltage / at DC / rated value                                                               | 600 V                       |
| operating voltage / at AC / rated value                                                               | 690 V                       |
| power loss [W] / maximum                                                                              | 10.6 W                      |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole           | 3.53 W                      |
| mechanical service life (operating cycles) / typical                                                  | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 9 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                          | 6 300                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No                          |
| ground-fault monitoring version                                                                       | Without                     |
| product function                                                                                      |                             |
| • communication function                                                                              | No                          |
| • other measurement function                                                                          | No                          |
| Net Weight                                                                                            | 1.195 kg                    |
| Current                                                                                               |                             |
| operational current                                                                                   |                             |
| • at 40 °C                                                                                            | 16 A                        |
| • at 45 °C                                                                                            | 16 A                        |
| • at 50 °C                                                                                            | 16 A                        |
| • at 55 °C                                                                                            | 16 A                        |
| • at 60 °C                                                                                            | 15 A                        |
| • at 65 °C                                                                                            | 15 A                        |
| • at 70 °C                                                                                            | 15 A                        |
| Switching capacity according to IEC 60947                                                             |                             |
| switching capacity class of the circuit breaker                                                       | S                           |
| maximum short-circuit current breaking capacity ( $I_{cu}$ )                                          |                             |
| • at 240 V                                                                                            | 55 kA                       |
| • at 415 V                                                                                            | 36 kA                       |
| • at 440 V                                                                                            | 25 kA                       |

|                                                                                                                                              |                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 500 V</li> <li>• at 690 V</li> </ul>                                                             | 7 kA                                                                                                                                                           |
| operating short-circuit current breaking capacity (Ics)                                                                                      | 7 kA                                                                                                                                                           |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 55 kA                                                                                                                                                          |
|                                                                                                                                              | 36 kA                                                                                                                                                          |
|                                                                                                                                              | 25 kA                                                                                                                                                          |
|                                                                                                                                              | 5 kA                                                                                                                                                           |
|                                                                                                                                              | 5 kA                                                                                                                                                           |
| short-circuit current making capacity (Icm)                                                                                                  |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 121 kA                                                                                                                                                         |
|                                                                                                                                              | 75.6 kA                                                                                                                                                        |
|                                                                                                                                              | 52.5 kA                                                                                                                                                        |
|                                                                                                                                              | 11.9 kA                                                                                                                                                        |
|                                                                                                                                              | 11.9 kA                                                                                                                                                        |
| design of short-circuit protection                                                                                                           | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |
| <b>Adjustable parameters</b>                                                                                                                 |                                                                                                                                                                |
| product feature / for L-tripping / can be switched on/off                                                                                    | No                                                                                                                                                             |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic                                                     |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                                               | 16 A                                                                                                                                                           |
|                                                                                                                                              | 16 A                                                                                                                                                           |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic                                                         |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                                               | 1 s                                                                                                                                                            |
|                                                                                                                                              | 1 s                                                                                                                                                            |
| adjustable response value setting current (Ii) / for I-tripping                                                                              |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                                               | 320 A                                                                                                                                                          |
|                                                                                                                                              | 320 A                                                                                                                                                          |
| adjustable setting current (InN) / for N-tripping                                                                                            |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                                               | 0 A                                                                                                                                                            |
|                                                                                                                                              | 0 A                                                                                                                                                            |
| design of the N-conductor protection                                                                                                         | without                                                                                                                                                        |
| product function / grounding protection                                                                                                      | No                                                                                                                                                             |
| <b>Mechanical Design</b>                                                                                                                     |                                                                                                                                                                |
| product component                                                                                                                            |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul>                | No                                                                                                                                                             |
|                                                                                                                                              | No                                                                                                                                                             |
|                                                                                                                                              | No                                                                                                                                                             |
| height [in]                                                                                                                                  | 5.12 in                                                                                                                                                        |
| height                                                                                                                                       | 130 mm                                                                                                                                                         |
| width [in]                                                                                                                                   | 4 in                                                                                                                                                           |
| width                                                                                                                                        | 101.6 mm                                                                                                                                                       |
| depth [in]                                                                                                                                   | 2.76 in                                                                                                                                                        |
| depth                                                                                                                                        | 70 mm                                                                                                                                                          |
| <b>Connections</b>                                                                                                                           |                                                                                                                                                                |
| arrangement of electrical connectors / for main current circuit                                                                              | Front terminal                                                                                                                                                 |
| type of electrical connection / for main current circuit                                                                                     | nut keeper kit on both ends                                                                                                                                    |
| type of connectable conductor cross-sections / for flat-bar terminal connection / minimum                                                    | 12 x 1 mm                                                                                                                                                      |
| type of connectable conductor cross-sections / for flat-bar terminal connection / maximum                                                    | 17 x 6,5 mm                                                                                                                                                    |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)                                                           | Silver                                                                                                                                                         |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)                                                        | Tin                                                                                                                                                            |
| <b>Auxiliary circuit</b>                                                                                                                     |                                                                                                                                                                |
| number of CO contacts / for auxiliary contacts                                                                                               | 0                                                                                                                                                              |
| <b>Accessories</b>                                                                                                                           |                                                                                                                                                                |
| product extension / optional / motor drive                                                                                                   | Yes                                                                                                                                                            |

| Environmental conditions           |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

| Environmental footprint                                  |           |
|----------------------------------------------------------|-----------|
| Environmental Product Declaration(EPD)                   | Yes       |
| global warming potential [CO2 eq] / total                | 190 kg    |
| global warming potential [CO2 eq] / during manufacturing | 4.67 kg   |
| global warming potential [CO2 eq] / during operation     | 186 kg    |
| global warming potential [CO2 eq] / after end of life    | -0.826 kg |
| reference code / according to IEC 81346-2                | Q         |

| Approvals / Certificates |  |
|--------------------------|--|
| General Product Approval |  |



[Miscellaneous](#)

[KC](#)

| General Product Approval | EMV | Test Certificates |
|--------------------------|-----|-------------------|
|--------------------------|-----|-------------------|



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

| Maritime application |  |
|----------------------|--|
|----------------------|--|



[CCS \(China Classification Society\)](#)

| other | Environment |
|-------|-------------|
|-------|-------------|



[Confirmation](#)

[Miscellaneous](#)



[Environmental Confirmations](#)



| Environment |
|-------------|
|-------------|

[Environmental Confirmations](#)

| Further information |
|---------------------|
|---------------------|

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA1196-4ED42-0AA0>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)


<https://support.industry.siemens.com/cs/ww/en/ps/3VA1196-4ED42-0AA0>

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA1196-4ED42-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA1196-4ED42-0AA0)

<https://www.siemens.com/cax>

<https://www.siemens.com/specifications>





last modified:

8/7/2025

