

**Siemens  
EcoTech**



circuit breaker 3VA2 IEC Frame 160 breaking capacity class L Icu=150 kA @ 415 V 4-pole, line protection ETU550, LSI, In=160 A overload protection Ir=63 A...160 A short-circuit protection Isd=0.6..10x In, li=1.5..10x In neutral conductor protection adjustable (OFF, up to 100%) nut keeper kit



| Model                                                                                                 |                             |
|-------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                    | SENTRON                     |
| product designation                                                                                   | Molded case circuit breaker |
| design of the product                                                                                 | Line protection             |
| design of the overcurrent release                                                                     | ETU550                      |
| protection function of the overcurrent release                                                        | LSI                         |
| number of poles                                                                                       | 4                           |
| General technical data                                                                                |                             |
| insulation voltage / rated value                                                                      | 800 V                       |
| operating voltage / at AC / rated value                                                               | 690 V                       |
| power loss [W] / maximum                                                                              | 19.7 W                      |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole           | 6.57 W                      |
| mechanical service life (operating cycles) / typical                                                  | 25 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 14 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                          | 9 800                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No                          |
| ground-fault monitoring version                                                                       | Without                     |
| product function                                                                                      |                             |
| • communication function                                                                              | Yes                         |
| • other measurement function                                                                          | No                          |
| Net Weight                                                                                            | 3.2 kg                      |
| Current                                                                                               |                             |
| operational current                                                                                   |                             |
| • at 40 °C                                                                                            | 160 A                       |
| • at 45 °C                                                                                            | 160 A                       |
| • at 50 °C                                                                                            | 160 A                       |
| • at 55 °C                                                                                            | 160 A                       |
| • at 60 °C                                                                                            | 160 A                       |
| • at 65 °C                                                                                            | 160 A                       |
| • at 70 °C                                                                                            | 160 A                       |
| Switching capacity according to IEC 60947                                                             |                             |
| switching capacity class of the circuit breaker                                                       | L                           |
| maximum short-circuit current breaking capacity (Icu)                                                 |                             |
| • at 240 V                                                                                            | 200 kA                      |

|                                                                                                                                                                                                      |                                                 |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul>                                                                             | 150 kA<br>150 kA<br>100 kA<br>25 kA             |
| operating short-circuit current breaking capacity (Ics) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 200 kA<br>150 kA<br>150 kA<br>100 kA<br>18 kA   |
| short-circuit current making capacity (Icm) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul>             | 440 kA<br>330 kA<br>330 kA<br>220 kA<br>52.5 kA |

#### Adjustable parameters

|                                                                                                                                                                         |                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product feature / for L-tripping / can be switched on/off                                                                                                               | No                          |
| adjustable response value setting current (Ir) / of the L-trip / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul> | 64 A<br>160 A               |
| adjustable response value delay time (tr) / for L-tripping / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>     | 0.5 s<br>20 s               |
| adjustable response value setting current (Isd) / of S-trip / with I0t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>    | 96 A<br>1 600 A             |
| adjustable response value setting current (Isd) / of S-trip / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>    | 96 A<br>1 600 A             |
| adjustable response value delay time (tsd) / for S-tripping / with I0t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>    | 0.05 s<br>0.5 s             |
| adjustable response value delay time (tsd) / for S-tripping / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>    | 0.05 s<br>0.5 s             |
| adjustable response value setting current (Ii) / for I-tripping <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                          | 240 A<br>1 600 A            |
| adjustable setting current (InN) / for N-tripping <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                        | 32 A<br>160 A               |
| design of the N-conductor protection                                                                                                                                    | adjustable OFF; 20% to 100% |
| product function / grounding protection                                                                                                                                 | No                          |

#### Mechanical Design

|                                                                                                                                                 |                |
|-------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| product component <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul> | No<br>No<br>No |
| height [in]                                                                                                                                     | 7.13 in        |
| height                                                                                                                                          | 181 mm         |
| width [in]                                                                                                                                      | 5.51 in        |
| width                                                                                                                                           | 140 mm         |
| depth [in]                                                                                                                                      | 3.39 in        |
| depth                                                                                                                                           | 86 mm          |

| Connections                                                                               |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| arrangement of electrical connectors / for main current circuit                           | Front terminal                                                                      |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| type of electrical connection / for main current circuit                                  | on both sides nut keeper kit                                                        |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| type of connectable conductor cross-sections / for flat-bar terminal connection / minimum | 13 x 1 mm                                                                           |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| type of connectable conductor cross-sections / for flat-bar terminal connection / maximum | 25 x 8 mm                                                                           |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)        | tin                                                                                 |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)     | tin                                                                                 |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| Auxiliary circuit                                                                         |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| number of CO contacts / for auxiliary contacts                                            | 0                                                                                   |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| Accessories                                                                               |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| product extension / optional / motor drive                                                | Yes                                                                                 |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| Environmental conditions                                                                  |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| protection class IP / on the front                                                        | IP40                                                                                |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| ambient temperature                                                                       |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| • during operation / minimum                                                              | -25 °C                                                                              |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| • during operation / maximum                                                              | 70 °C                                                                               |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| • during storage / minimum                                                                | -40 °C                                                                              |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| • during storage / maximum                                                                | 80 °C                                                                               |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| Environmental footprint                                                                   |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| global warming potential [CO2 eq] / total                                                 | 61.814 kg                                                                           |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| global warming potential [CO2 eq] / during manufacturing                                  | 14.6 kg                                                                             |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| global warming potential [CO2 eq] / during operation                                      | 48.9 kg                                                                             |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| global warming potential [CO2 eq] / after end of life                                     | -2.2 kg                                                                             |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| Siemens Eco Profile (SEP)                                                                 | Siemens EcoTech                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| reference code / according to IEC 81346-2                                                 | Q                                                                                   |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| Approvals / Certificates                                                                  |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
| General Product Approval                                                                  |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |
|        |  |  |  | <a href="#">Miscellaneous</a>                                                         |  |
| General Product Approval                                                                  | EMV                                                                                 | Test Certificates                                                                   |                                                                                     | Maritime application                                                                  |                                                                                       |
|        |  | <a href="#">Type Test Certificates/Test Report</a>                                  | <a href="#">Miscellaneous</a>                                                       | <a href="#">Special Test Certificate</a>                                              |  |
| Maritime application                                                                      |                                                                                     |                                                                                     |                                                                                     |                                                                                       | other                                                                                 |
|        |  |  |  | <a href="#">CCS (China Classification Society)</a>                                    |  |
| other                                                                                     | Dangerous goods                                                                     |                                                                                     | Environment                                                                         |                                                                                       |                                                                                       |
| <a href="#">Confirmation</a>                                                              | <a href="#">Miscellaneous</a>                                                       | <a href="#">Transport Information</a>                                               |  |  | <a href="#">Environmental Confirmations</a>                                           |
| Environment                                                                               |                                                                                     |                                                                                     |                                                                                     |                                                                                       |                                                                                       |

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2116-8JP42-0AA0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2116-8JP42-0AA0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA2116-8JP42-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2116-8JP42-0AA0)

### CAX-Online-Generator

<https://www.siemens.com/cax>

### Tender specifications

<https://www.siemens.com/specifications>





