

Siemens  
EcoTech



circuit breaker 3VA2 IEC Frame 400 breaking capacity class C Icu=110 kA @ 415 V 3-pole, line protection ETU350, LSI, In=250 A overload protection Ir=100 A...250 A short-circuit protection Isd=1.5...10 x Ir, li=12 x In nut keeper kit



| Model                                                                                                 |                             |
|-------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                    | SENTRON                     |
| product designation                                                                                   | Molded case circuit breaker |
| design of the product                                                                                 | Line protection             |
| design of the overcurrent release                                                                     | ETU350                      |
| protection function of the overcurrent release                                                        | LSI                         |
| number of poles                                                                                       | 3                           |
| General technical data                                                                                |                             |
| insulation voltage / rated value                                                                      | 800 V                       |
| operating voltage / at AC / rated value                                                               | 690 V                       |
| power loss [W] / maximum                                                                              | 37.5 W                      |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole           | 12.5 W                      |
| mechanical service life (operating cycles) / typical                                                  | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                      | 6 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                          | 4 200                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof | No                          |
| ground-fault monitoring version                                                                       | Without                     |
| product function                                                                                      |                             |
| • communication function                                                                              | No                          |
| • other measurement function                                                                          | No                          |
| Net Weight                                                                                            | 4.672 kg                    |
| Current                                                                                               |                             |
| operational current                                                                                   |                             |
| • at 40 °C                                                                                            | 250 A                       |
| • at 45 °C                                                                                            | 250 A                       |
| • at 50 °C                                                                                            | 250 A                       |
| • at 55 °C                                                                                            | 250 A                       |
| • at 60 °C                                                                                            | 250 A                       |
| • at 65 °C                                                                                            | 250 A                       |
| • at 70 °C                                                                                            | 250 A                       |
| Switching capacity according to IEC 60947                                                             |                             |
| switching capacity class of the circuit breaker                                                       | C                           |
| maximum short-circuit current breaking capacity (Icu)                                                 |                             |
| • at 240 V                                                                                            | 150 kA                      |

|                                                                                                                                                                                                      |                                                |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul>                                                                             | 110 kA<br>110 kA<br>85 kA<br>5 kA              |
| operating short-circuit current breaking capacity (Ics) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul> | 150 kA<br>110 kA<br>110 kA<br>65 kA<br>5 kA    |
| short-circuit current making capacity (Icm) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 440 V</li> <li>• at 500 V</li> <li>• at 690 V</li> </ul>             | 330 kA<br>242 kA<br>242 kA<br>187 kA<br>7.5 kA |
| <b>Adjustable parameters</b>                                                                                                                                                                         |                                                |
| product feature / for L-tripping / can be switched on/off                                                                                                                                            | No                                             |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                 | 100 A<br>250 A                                 |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                     | 0.5 s<br>17 s                                  |
| adjustable response value setting current (I <sub>sd</sub> ) / of S-trip / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                    | 150 A<br>2 500 A                               |
| adjustable response value delay time (t <sub>sd</sub> ) / for S-tripping / with I2t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                    | 0.0001 s<br>0.4 s                              |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                          | 3 000 A<br>3 000 A                             |
| adjustable setting current (I <sub>nN</sub> ) / for N-tripping <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                                        | 0 A<br>0 A                                     |
| product function / grounding protection                                                                                                                                                              | No                                             |
| <b>Mechanical Design</b>                                                                                                                                                                             |                                                |
| product component <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul>                                                      | No<br>No<br>No                                 |
| height [in]                                                                                                                                                                                          | 9.76 in                                        |
| height                                                                                                                                                                                               | 248 mm                                         |
| width [in]                                                                                                                                                                                           | 5.43 in                                        |
| width                                                                                                                                                                                                | 138 mm                                         |
| depth [in]                                                                                                                                                                                           | 4.33 in                                        |
| depth                                                                                                                                                                                                | 110 mm                                         |
| <b>Connections</b>                                                                                                                                                                                   |                                                |
| arrangement of electrical connectors / for main current circuit                                                                                                                                      | Front terminal                                 |
| type of electrical connection / for main current circuit                                                                                                                                             | on both sides nut keeper kit                   |
| type of connectable conductor cross-sections / for flat-bar terminal connection / minimum                                                                                                            | 20 x 1 mm                                      |
| type of connectable conductor cross-sections / for flat-bar terminal connection / maximum                                                                                                            | 35 x 10 mm                                     |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)                                                                                                                   | silver                                         |

|                                                                                       |                 |
|---------------------------------------------------------------------------------------|-----------------|
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | silver          |
| <b>Auxiliary circuit</b>                                                              |                 |
| number of CO contacts / for auxiliary contacts                                        | 0               |
| <b>Accessories</b>                                                                    |                 |
| product extension / optional / motor drive                                            | Yes             |
| <b>Environmental conditions</b>                                                       |                 |
| protection class IP / on the front                                                    | IP40            |
| ambient temperature                                                                   |                 |
| • during operation / minimum                                                          | -25 °C          |
| • during operation / maximum                                                          | 70 °C           |
| • during storage / minimum                                                            | -40 °C          |
| • during storage / maximum                                                            | 80 °C           |
| <b>Environmental footprint</b>                                                        |                 |
| global warming potential [CO2 eq] / total                                             | 495 kg          |
| global warming potential [CO2 eq] / during manufacturing                              | 28.7 kg         |
| global warming potential [CO2 eq] / during operation                                  | 470 kg          |
| global warming potential [CO2 eq] / after end of life                                 | -4.07 kg        |
| Siemens Eco Profile (SEP)                                                             | Siemens EcoTech |
| reference code / according to IEC 81346-2                                             | Q               |
| <b>Approvals / Certificates</b>                                                       |                 |
| <b>General Product Approval</b>                                                       |                 |



[Confirmation](#)



[Miscellaneous](#)



| General Product Approval                                                            | EMV                                                                                 | Test Certificates                        | Maritime application                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------|
|  |  | <a href="#">Special Test Certificate</a> | <a href="#">Miscellaneous</a>                                                         |
|                                                                                     |                                                                                     |                                          |  |
|                                                                                     |                                                                                     |                                          |  |

| Maritime application                                                                | other                                                                                 |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |    |
|                                                                                     |    |
|                                                                                     | <a href="#">CCS (China Classification Society)</a>                                    |
|                                                                                     |  |
|                                                                                     | <a href="#">Confirmation</a>                                                          |

| other                         | Dangerous goods                       | Environment                                                                          |
|-------------------------------|---------------------------------------|--------------------------------------------------------------------------------------|
| <a href="#">Miscellaneous</a> | <a href="#">Transport Information</a> |   |
|                               |                                       |  |
|                               |                                       | <a href="#">Environmental Confirmations</a>                                          |
|                               |                                       | <a href="#">Environmental Confirmations</a>                                          |

|                                                                                                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Further information</b>                                                                                                                                                                                                        |
| Information on the packaging<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>                                                           |
| Information for data generation and storage<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109995012">https://support.industry.siemens.com/cs/ww/en/view/109995012</a>                                            |
| Information- and Downloadcenter (Catalogs, Brochures,...)<br><a href="https://www.siemens.com/lowvoltage/catalogs">https://www.siemens.com/lowvoltage/catalogs</a>                                                                |
| Industry Mall (Online ordering system)<br><a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2325-7HN32-0AA0">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2325-7HN32-0AA0</a> |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<br><a href="https://support.industry.siemens.com/cs/ww/en/ps/3VA2325-7HN32-0AA0">https://support.industry.siemens.com/cs/ww/en/ps/3VA2325-7HN32-0AA0</a>       |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)                                                                                                                                   |





