



circuit breaker 3VA5 UL Frame 250 breaking capacity class H 65 kA @ 480 V 4-pole, line protection TM210, FTFM,  $I_n=60$  A overload protection, 100%-rated  $I_r=60$  A permanently set short-circuit protection  $I_i=10 \times I_n$  N conductor unprotected without connection

| Model                                                                                                                      |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SENTRON                     |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | HFAS                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the load switch / according to UL 489 / High-Intensity-Discharge circuit breaker (HID Type)                      | No                          |
| design of the load switch / according to UL 489 / Switching Duty circuit breaker (SWD Type)                                | No                          |
| design of the overcurrent release                                                                                          | TM210                       |
| protection function of the overcurrent release                                                                             | LI                          |
| number of poles                                                                                                            | 4                           |
| General technical data                                                                                                     |                             |
| insulation voltage / rated value                                                                                           | 800 V                       |
| operating voltage / at DC / rated value                                                                                    | 1 000 V                     |
| operating voltage / at AC / rated value                                                                                    | 690 V                       |
| power loss [W] / maximum                                                                                                   | 22 W                        |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 7.3 W                       |
| mechanical service life (operating cycles) / typical                                                                       | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 8 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 4 000                       |
| electrical endurance (operating cycles) / at 480 V                                                                         | 8 000                       |
| electrical endurance (operating cycles) / at 600 V                                                                         | 4 000                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof                      | No                          |
| product function                                                                                                           |                             |
| • communication function                                                                                                   | No                          |
| • other measurement function                                                                                               | No                          |
| Net Weight                                                                                                                 | 2 800 g                     |
| Current                                                                                                                    |                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | Yes                         |
| operational current                                                                                                        |                             |
| • at 40 °C                                                                                                                 | 60 A                        |
| • at 45 °C                                                                                                                 | 58.6 A                      |
| • at 50 °C                                                                                                                 | 57.2 A                      |
| • at 55 °C                                                                                                                 | 55.7 A                      |
| • at 60 °C                                                                                                                 | 54.3 A                      |

|                                                                                                                                                                                                   |                                                                                                                                                                |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• at 65 °C</li> <li>• at 70 °C</li> </ul>                                                                                                                  | 52.9 A<br>51.5 A                                                                                                                                               |
| <b>Switching capacity according to IEC 60947</b>                                                                                                                                                  |                                                                                                                                                                |
| switching capacity class of the circuit breaker                                                                                                                                                   | H                                                                                                                                                              |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> ) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 690 V</li> </ul>                           | 100 kA<br>70 kA<br>10 kA                                                                                                                                       |
| operating short-circuit current breaking capacity (I <sub>cs</sub> ) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 690 V</li> </ul>                         | 100 kA<br>70 kA<br>10 kA                                                                                                                                       |
| short-circuit current making capacity (I <sub>cm</sub> ) <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 415 V</li> <li>• at 690 V</li> </ul>                                     | 220 kA<br>154 kA<br>17 kA                                                                                                                                      |
| design of short-circuit protection                                                                                                                                                                | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |
| <b>Switching capacity according to UL 489</b>                                                                                                                                                     |                                                                                                                                                                |
| current breaking capacity <ul style="list-style-type: none"> <li>• at 240 V</li> <li>• at 480 V</li> <li>• at 600 V</li> </ul>                                                                    | 100 kA<br>65 kA<br>25 kA                                                                                                                                       |
| <b>Adjustable parameters</b>                                                                                                                                                                      |                                                                                                                                                                |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sup>2</sup> t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul> | 60 A<br>60 A                                                                                                                                                   |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sup>2</sup> t characteristic <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>     | 1 s<br>1 s                                                                                                                                                     |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                       | 600 A<br>600 A                                                                                                                                                 |
| adjustable setting current (I <sub>nN</sub> ) / for N-tripping <ul style="list-style-type: none"> <li>• minimum</li> <li>• maximum</li> </ul>                                                     | 0 A<br>0 A                                                                                                                                                     |
| design of the N-conductor protection                                                                                                                                                              | Without                                                                                                                                                        |
| product function / grounding protection                                                                                                                                                           | No                                                                                                                                                             |
| <b>Mechanical Design</b>                                                                                                                                                                          |                                                                                                                                                                |
| product component <ul style="list-style-type: none"> <li>• undervoltage release</li> <li>• voltage trigger</li> <li>• trip indicator</li> </ul>                                                   | No<br>No<br>No                                                                                                                                                 |
| height [in]                                                                                                                                                                                       | 7.28 in                                                                                                                                                        |
| height                                                                                                                                                                                            | 185 mm                                                                                                                                                         |
| width [in]                                                                                                                                                                                        | 5.51 in                                                                                                                                                        |
| width                                                                                                                                                                                             | 140 mm                                                                                                                                                         |
| depth [in]                                                                                                                                                                                        | 3.27 in                                                                                                                                                        |
| depth                                                                                                                                                                                             | 83 mm                                                                                                                                                          |
| <b>Connections</b>                                                                                                                                                                                |                                                                                                                                                                |
| arrangement of electrical connectors / for main current circuit                                                                                                                                   | Without connection                                                                                                                                             |
| type of electrical connection / for main current circuit                                                                                                                                          | Without                                                                                                                                                        |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)                                                                                                             | silver                                                                                                                                                         |
| <b>Auxiliary circuit</b>                                                                                                                                                                          |                                                                                                                                                                |
| number of CO contacts / for auxiliary contacts                                                                                                                                                    | 0                                                                                                                                                              |
| <b>Accessories</b>                                                                                                                                                                                |                                                                                                                                                                |

|                                            |                                  |
|--------------------------------------------|----------------------------------|
| product extension / optional / motor drive | Yes                              |
| manufacturer's article number              |                                  |
| • of the supplied basic switch             | <a href="#">3VA52606ED412AA0</a> |
| <b>Environmental conditions</b>            |                                  |
| protection class IP / on the front         | IP40                             |
| ambient temperature                        |                                  |
| • during operation / minimum               | -25 °C                           |
| • during operation / maximum               | 70 °C                            |
| • during storage / minimum                 | -40 °C                           |
| • during storage / maximum                 | 80 °C                            |
| reference code / according to IEC 81346-2  | Q                                |
| <b>Approvals / Certificates</b>            |                                  |
| <b>General Product Approval</b>            |                                  |



[Miscellaneous](#)



| General Product Approval                                                          | EMV                                                                               | other                         | Environment                                 |
|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------|---------------------------------------------|
|  |  | <a href="#">Confirmation</a>  | <a href="#">Confirmation</a>                |
|                                                                                   | RCM                                                                               | <a href="#">Miscellaneous</a> | <a href="#">Environmental Confirmations</a> |

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA5260-6ED41-2AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA5260-6ED41-2AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA5260-6ED41-2AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA5260-6ED41-2AA0)

##### CAX-Online-Generator

<https://www.siemens.com/cax>

##### Tender specifications

<https://www.siemens.com/specifications>





