



circuit breaker 3VA5 UL Frame 400 breaking capacity class C 100 kA @ 480 V 3-pole, line protection TM230, FTAM,  $I_n=300$  A overload protection  $I_r=300$  A permanently set short-circuit protection  $I_i=5...10 \times I_n$  UL 489 SB (naval), 50 °C, without connection

| Model                                                                                                                      |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SETRON                      |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | CJAM                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the load switch / according to UL 489 / High-Intensity-Discharge circuit breaker (HID Type)                      | No                          |
| design of the load switch / according to UL 489 / Switching Duty circuit breaker (SWD Type)                                | No                          |
| design of the overcurrent release                                                                                          | TM230                       |
| protection function of the overcurrent release                                                                             | LI                          |
| number of poles                                                                                                            | 3                           |
| General technical data                                                                                                     |                             |
| power loss [W] / maximum                                                                                                   | 70 W                        |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 23.4 W                      |
| mechanical service life (operating cycles) / typical                                                                       | 20 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 6 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 3 000                       |
| electrical endurance (operating cycles) / at 480 V                                                                         | 6 000                       |
| electrical endurance (operating cycles) / at 600 V                                                                         | 3 000                       |
| product feature / for neutral conductors / upgradable/retrofittable / short-circuit and overload proof                     | No                          |
| product function                                                                                                           |                             |
| • communication function                                                                                                   | No                          |
| • other measurement function                                                                                               | No                          |
| Net Weight                                                                                                                 | 5.2 kg                      |
| Current                                                                                                                    |                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | No                          |
| operational current                                                                                                        |                             |
| • at 40 °C                                                                                                                 | 300 A                       |
| • at 45 °C                                                                                                                 | 294 A                       |
| • at 50 °C                                                                                                                 | 288 A                       |
| • at 55 °C                                                                                                                 | 282 A                       |
| • at 60 °C                                                                                                                 | 276 A                       |
| • at 65 °C                                                                                                                 | 270 A                       |
| • at 70 °C                                                                                                                 | 264 A                       |
| Switching capacity according to IEC 60947                                                                                  |                             |

|                                                                                                                                                                                                          |                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| switching capacity class of the circuit breaker                                                                                                                                                          | C                                                                                                                                                              |
| design of short-circuit protection                                                                                                                                                                       | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |
| <b>Switching capacity according to UL 489</b>                                                                                                                                                            |                                                                                                                                                                |
| current breaking capacity <ul style="list-style-type: none"> <li>at 240 V</li> <li>at 480 V</li> <li>at 600 V</li> </ul>                                                                                 | 200 kA<br>100 kA<br>35 kA                                                                                                                                      |
| <b>Adjustable parameters</b>                                                                                                                                                                             |                                                                                                                                                                |
| adjustable response value setting current ( $I_r$ ) / of the L-trip / with I2t characteristic <ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>                                 | 300 A<br>300 A                                                                                                                                                 |
| adjustable response value delay time ( $t_r$ ) / for L-tripping / with I2t characteristic <ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>                                     | 1 s<br>1 s                                                                                                                                                     |
| adjustable response value setting current ( $I_l$ ) / for I-tripping <ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>                                                          | 1 500 A<br>3 000 A                                                                                                                                             |
| adjustable setting current ( $I_{nN}$ ) / for N-tripping <ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>                                                                      | 0 A<br>0 A                                                                                                                                                     |
| product function / grounding protection                                                                                                                                                                  | No                                                                                                                                                             |
| <b>Mechanical Design</b>                                                                                                                                                                                 |                                                                                                                                                                |
| product component <ul style="list-style-type: none"> <li>undervoltage release</li> <li>voltage trigger</li> <li>trip indicator</li> </ul>                                                                | No<br>No<br>No                                                                                                                                                 |
| height [in]                                                                                                                                                                                              | 9.76 in                                                                                                                                                        |
| height                                                                                                                                                                                                   | 248 mm                                                                                                                                                         |
| width [in]                                                                                                                                                                                               | 5.43 in                                                                                                                                                        |
| width                                                                                                                                                                                                    | 138 mm                                                                                                                                                         |
| depth [in]                                                                                                                                                                                               | 4.33 in                                                                                                                                                        |
| depth                                                                                                                                                                                                    | 110 mm                                                                                                                                                         |
| <b>Connections</b>                                                                                                                                                                                       |                                                                                                                                                                |
| arrangement of electrical connectors / for main current circuit                                                                                                                                          | Without connection                                                                                                                                             |
| type of electrical connection / for main current circuit                                                                                                                                                 | Without                                                                                                                                                        |
| <b>Auxiliary circuit</b>                                                                                                                                                                                 |                                                                                                                                                                |
| number of CO contacts / for auxiliary contacts                                                                                                                                                           | 0                                                                                                                                                              |
| <b>Accessories</b>                                                                                                                                                                                       |                                                                                                                                                                |
| product extension / optional / motor drive                                                                                                                                                               | Yes                                                                                                                                                            |
| <b>Environmental conditions</b>                                                                                                                                                                          |                                                                                                                                                                |
| protection class IP / on the front                                                                                                                                                                       | IP40                                                                                                                                                           |
| ambient temperature <ul style="list-style-type: none"> <li>during operation / minimum</li> <li>during operation / maximum</li> <li>during storage / minimum</li> <li>during storage / maximum</li> </ul> | -25 °C<br>70 °C<br>-40 °C<br>80 °C                                                                                                                             |
| reference code / according to IEC 81346-2                                                                                                                                                                | Q                                                                                                                                                              |
| <b>Approvals / Certificates</b>                                                                                                                                                                          |                                                                                                                                                                |
| <b>General Product Approval</b>                                                                                                                                                                          |                                                                                                                                                                |



[Confirmation](#)



[Miscellaneous](#)[Confirmation](#)[Miscellaneous](#)

## Environment

[Environmental Conformations](#)

## Further information

## Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

## Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

## Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

## Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA5330-7EC31-1AA0>

## Service&amp;Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA5330-7EC31-1AA0>

## Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA5330-7EC31-1AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA5330-7EC31-1AA0)

## CAx-Online-Generator

<https://www.siemens.com/cax>

## Tender specifications

<https://www.siemens.com/specifications>





