



circuit breaker 3VA5 UL frame 1200 breaking capacity class H 65kA @ 480 V 2-pole, line protection TM230, FTAM, In=900A 100%-rated, overload protection Ir=900A fixed short circuit protection li=5 - 10 x In w/o connection

| Model                                                                                                                      |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SETRON                      |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | HNAS                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the overcurrent release                                                                                          | TM230                       |
| protection function of the overcurrent release                                                                             | LI                          |
| number of poles                                                                                                            | 2                           |
| General technical data                                                                                                     |                             |
| insulation voltage / rated value                                                                                           | 800 V                       |
| operating voltage / at DC / rated value                                                                                    | 500 V                       |
| operating voltage / at AC / rated value                                                                                    | 600 V                       |
| power loss [W] / maximum                                                                                                   | 167 W                       |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 167 W                       |
| mechanical service life (operating cycles) / typical                                                                       | 3 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 1 500                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 500                         |
| electrical endurance (operating cycles) / at 480 V                                                                         | 1 500                       |
| electrical endurance (operating cycles) / at 600 V                                                                         | 500                         |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof                      | No                          |
| product function                                                                                                           |                             |
| • communication function                                                                                                   | No                          |
| • phase failure detection                                                                                                  | No                          |
| • other measurement function                                                                                               | No                          |
| Net Weight                                                                                                                 | 3.133 kg                    |
| Current                                                                                                                    |                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | Yes                         |
| operational current                                                                                                        |                             |
| • at 40 °C                                                                                                                 | 900 A                       |
| • at 45 °C                                                                                                                 | 868 A                       |
| • at 50 °C                                                                                                                 | 837 A                       |
| • at 55 °C                                                                                                                 | 805 A                       |
| • at 60 °C                                                                                                                 | 774 A                       |
| • at 65 °C                                                                                                                 | 742 A                       |
| • at 70 °C                                                                                                                 | 710 A                       |
| Switching capacity according to IEC 60947                                                                                  |                             |

|                                                                      |                                                                                                                                                                |
|----------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| switching capacity class of the circuit breaker                      | H                                                                                                                                                              |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )   |                                                                                                                                                                |
| • at 240 V                                                           | 110 kA                                                                                                                                                         |
| • at 415 V                                                           | 70 kA                                                                                                                                                          |
| • at 690 V                                                           | 30 kA                                                                                                                                                          |
| operating short-circuit current breaking capacity (I <sub>cs</sub> ) |                                                                                                                                                                |
| • at 240 V                                                           | 55 kA                                                                                                                                                          |
| • at 415 V                                                           | 35 kA                                                                                                                                                          |
| • at 690 V                                                           | 15 kA                                                                                                                                                          |
| short-circuit current making capacity (I <sub>cm</sub> )             |                                                                                                                                                                |
| • at 240 V                                                           | 242 kA                                                                                                                                                         |
| • at 415 V                                                           | 154 kA                                                                                                                                                         |
| • at 690 V                                                           | 63 kA                                                                                                                                                          |
| design of short-circuit protection                                   | For switching power values in DC networks, see the 3VA molded case circuit breaker device manual; link to be found under Service & Support in the last chapter |

#### Switching capacity according to UL 489

|                           |        |
|---------------------------|--------|
| current breaking capacity |        |
| • at 240 V                | 100 kA |
| • at 480 V                | 65 kA  |
| • at 600 Y/347 V          | 35 kA  |
| • at 600 V                | 35 kA  |

#### Adjustable parameters

|                                                                                                                   |         |
|-------------------------------------------------------------------------------------------------------------------|---------|
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic |         |
| • minimum                                                                                                         | 900 A   |
| • maximum                                                                                                         | 900 A   |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic     |         |
| • minimum                                                                                                         | 1 s     |
| • maximum                                                                                                         | 1 s     |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping                                      |         |
| • minimum                                                                                                         | 4 500 A |
| • maximum                                                                                                         | 9 000 A |
| product function / grounding protection                                                                           | No      |

#### Mechanical Design

|                        |          |
|------------------------|----------|
| product component      |          |
| • undervoltage release | No       |
| • trip indicator       | No       |
| height [in]            | 8.14 in  |
| height                 | 207 mm   |
| width [in]             | 8.99 in  |
| width                  | 228.4 mm |
| depth [in]             | 16 in    |
| depth                  | 406.4 mm |

#### Connections

|                                                                                       |                   |
|---------------------------------------------------------------------------------------|-------------------|
| type of electrical connection / for main current circuit                              | without terminals |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)    | silver            |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6) | silver            |

#### Auxiliary circuit

|                                                |   |
|------------------------------------------------|---|
| number of CO contacts / for auxiliary contacts | 0 |
|------------------------------------------------|---|

#### Environmental conditions

|                                    |        |
|------------------------------------|--------|
| protection class IP / on the front | IP40   |
| ambient temperature                |        |
| • during operation / minimum       | -25 °C |
| • during operation / maximum       | 70 °C  |
| • during storage / minimum         | -40 °C |
| • during storage / maximum         | 80 °C  |

|                                           |   |
|-------------------------------------------|---|
| reference code / according to IEC 81346-2 | F |
|-------------------------------------------|---|

## Approvals / Certificates

### General Product Approval



[Confirmation](#)



|                          |     |                   |                      |
|--------------------------|-----|-------------------|----------------------|
| General Product Approval | EMV | Test Certificates | Maritime application |
|--------------------------|-----|-------------------|----------------------|



[Miscellaneous](#)



[Type Test Certificates/Test Report](#)



|       |             |
|-------|-------------|
| other | Environment |
|-------|-------------|

[Confirmation](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

### Further information

#### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

#### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA5790-6EC61-2AA0>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA5790-6EC61-2AA0>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA5790-6EC61-2AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA5790-6EC61-2AA0)

#### CAX-Online-Generator

<https://www.siemens.com/cax>

#### Tender specifications

<https://www.siemens.com/specifications>



CB



last modified:

3/31/2025 

