

**Siemens  
EcoTech**



circuit breaker 3VA6 UL Frame 250 breaking capacity class C 100 kA @ 480 V 4-pole, line protection ETU830, LIG,  $I_n=100$  A overload protection  $I_r=40$  A...100 A short-circuit protection  $I_i=1.5...12 \times I_n$  ground-fault protection  $I_g=0.2...1 \times I_n$ ,  $t_g=0.05-0.8$ s without connection



| Model                                                                                                                      |                                             |
|----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|
| product brand name                                                                                                         | SENTRON                                     |
| product designation                                                                                                        | Molded-case circuit breaker                 |
| product designation / according to UL file                                                                                 | CFAE                                        |
| design of the product                                                                                                      | System protection                           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                                         |
| design of the overcurrent release                                                                                          | ETU830                                      |
| protection function of the overcurrent release                                                                             | LIG                                         |
| number of poles                                                                                                            | 4                                           |
| General technical data                                                                                                     |                                             |
| insulation voltage / rated value                                                                                           | 800 V                                       |
| operating voltage / at AC / rated value                                                                                    | 690 V                                       |
| power loss [W] / maximum                                                                                                   | 6.7 W                                       |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 2.23 W                                      |
| mechanical service life (operating cycles) / typical                                                                       | 25 000                                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 12 000                                      |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 8 400                                       |
| electrical endurance (operating cycles) / at 480 V                                                                         | 12 000                                      |
| electrical endurance (operating cycles) / at 600 V                                                                         | 8 400                                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof                      | No                                          |
| ground-fault monitoring version                                                                                            | Summation current formation L + N-conductor |
| product function                                                                                                           |                                             |
| • communication function                                                                                                   | Yes                                         |
| • other measurement function                                                                                               | Yes                                         |
| Net Weight                                                                                                                 | 3.2 kg                                      |
| Current                                                                                                                    |                                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | No                                          |
| operational current                                                                                                        |                                             |
| • at 40 °C                                                                                                                 | 100 A                                       |
| • at 45 °C                                                                                                                 | 100 A                                       |
| • at 50 °C                                                                                                                 | 100 A                                       |
| • at 55 °C                                                                                                                 | 100 A                                       |
| • at 60 °C                                                                                                                 | 100 A                                       |
| • at 65 °C                                                                                                                 | 100 A                                       |

|                                                                                                                    |                             |
|--------------------------------------------------------------------------------------------------------------------|-----------------------------|
| • at 70 °C                                                                                                         | 100 A                       |
| <b>Switching capacity according to IEC 60947</b>                                                                   |                             |
| switching capacity class of the circuit breaker                                                                    | C                           |
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )                                                 |                             |
| • at 240 V                                                                                                         | 150 kA                      |
| • at 415 V                                                                                                         | 110 kA                      |
| • at 690 V                                                                                                         | 3 kA                        |
| operating short-circuit current breaking capacity (I <sub>cs</sub> )                                               |                             |
| • at 240 V                                                                                                         | 150 kA                      |
| • at 415 V                                                                                                         | 110 kA                      |
| • at 690 V                                                                                                         | 3 kA                        |
| short-circuit current making capacity (I <sub>cm</sub> )                                                           |                             |
| • at 240 V                                                                                                         | 330 kA                      |
| • at 415 V                                                                                                         | 242 kA                      |
| • at 690 V                                                                                                         | 4.5 kA                      |
| <b>Switching capacity according to UL 489</b>                                                                      |                             |
| current breaking capacity                                                                                          |                             |
| • at 240 V                                                                                                         | 200 kA                      |
| • at 480 V                                                                                                         | 100 kA                      |
| • at 600 V                                                                                                         | 35 kA                       |
| <b>Adjustable parameters</b>                                                                                       |                             |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic  |                             |
| • minimum                                                                                                          | 40 A                        |
| • maximum                                                                                                          | 100 A                       |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic      |                             |
| • minimum                                                                                                          | 0.5 s                       |
| • maximum                                                                                                          | 25 s                        |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping                                       |                             |
| • minimum                                                                                                          | 150 A                       |
| • maximum                                                                                                          | 1 200 A                     |
| adjustable current response value current / for G-tripping / with standard characteristic                          |                             |
| • initial value                                                                                                    | 20 A                        |
| • full-scale value                                                                                                 | 100 A                       |
| adjustable response value delay time (t <sub>g</sub> ) / for G-tripping / with I <sub>0t</sub> characteristic      |                             |
| • minimum                                                                                                          | 0.05 s                      |
| • maximum                                                                                                          | 0.8 s                       |
| adjustable response value setting current (I <sub>g</sub> ) / for G-tripping / with I <sub>2t</sub> characteristic |                             |
| • minimum                                                                                                          | 20 A                        |
| • maximum                                                                                                          | 100 A                       |
| adjustable response value delay time (t <sub>g</sub> ) / for G-tripping / with I <sub>2t</sub> characteristic      |                             |
| • minimum                                                                                                          | 0.05 s                      |
| • maximum                                                                                                          | 0.8 s                       |
| adjustable setting current (I <sub>nN</sub> ) / for N-tripping                                                     |                             |
| • minimum                                                                                                          | 20 A                        |
| • maximum                                                                                                          | 160 A                       |
| design of the N-conductor protection                                                                               | adjustable OFF; 20% to 160% |
| product function / grounding protection                                                                            | Yes                         |
| <b>Mechanical Design</b>                                                                                           |                             |
| product component                                                                                                  |                             |
| • undervoltage release                                                                                             | No                          |
| • voltage trigger                                                                                                  | No                          |
| • trip indicator                                                                                                   | No                          |
| height [in]                                                                                                        | 7.8 in                      |
| height                                                                                                             | 198 mm                      |

|                                                                 |                    |
|-----------------------------------------------------------------|--------------------|
| width [in]                                                      | 5.51 in            |
| width                                                           | 140 mm             |
| depth [in]                                                      | 3.39 in            |
| depth                                                           | 86 mm              |
| <b>Connections</b>                                              |                    |
| arrangement of electrical connectors / for main current circuit | Without connection |
| type of electrical connection / for main current circuit        | Without            |
| <b>Auxiliary circuit</b>                                        |                    |
| number of CO contacts / for auxiliary contacts                  | 0                  |
| <b>Accessories</b>                                              |                    |
| product extension / optional / motor drive                      | Yes                |
| <b>Environmental conditions</b>                                 |                    |
| protection class IP / on the front                              | IP40               |
| ambient temperature                                             |                    |
| • during operation / minimum                                    | -25 °C             |
| • during operation / maximum                                    | 70 °C              |
| • during storage / minimum                                      | -40 °C             |
| • during storage / maximum                                      | 80 °C              |
| <b>Environmental footprint</b>                                  |                    |
| Environmental Product Declaration (EPD)                         | Yes                |
| global warming potential [CO2 eq] / total                       | 61.814 kg          |
| global warming potential [CO2 eq] / during manufacturing        | 14.6 kg            |
| global warming potential [CO2 eq] / during operation            | 48.9 kg            |
| global warming potential [CO2 eq] / after end of life           | -2.2 kg            |
| Siemens Eco Profile (SEP)                                       | Siemens EcoTech    |
| reference code / according to IEC 81346-2                       | Q                  |
| <b>Approvals / Certificates</b>                                 |                    |
| <b>General Product Approval</b>                                 |                    |



[Confirmation](#)



EG-Konf.



UL



UL

#### General Product Approval

#### EMV

#### Maritime application



VDE

[Miscellaneous](#)



RCM



ABS

#### Maritime application

#### other



BUREAU  
VERITAS



DNV



LRS



RMRS

[Confirmation](#)

[Miscellaneous](#)

#### Dangerous goods

#### Environment

[Transport Information](#)



Siemens  
EcoTech



[Environmental Con-  
firmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA6210-7KM41-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA6210-7KM41-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA6210-7KM41-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA6210-7KM41-0AA0)

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>





