



circuit breaker 3VA6 UL Frame 800 breaking capacity class C 100 kA @ 480 V 4-pole, line protection ETU350, LSI, In=600 A overload protection, 100% rated Ir=240 A ...600 A short-circuit protection Isd=1.5... 12 x Ir, li=12 x In neutral conductor protection adjustable (OFF, 50%, 100%) cable connection on two sides

| Model                                                                                                                      |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SENTRON                     |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | CMAE                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the overcurrent release                                                                                          | ETU350                      |
| protection function of the overcurrent release                                                                             | LSI                         |
| number of poles                                                                                                            | 4                           |
| General technical data                                                                                                     |                             |
| insulation voltage / rated value                                                                                           | 800 V                       |
| operating voltage / at AC / rated value                                                                                    | 690 V                       |
| power loss [W] / maximum                                                                                                   | 151 W                       |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 50.33 W                     |
| mechanical service life (operating cycles) / typical                                                                       | 10 000                      |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 5 100                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 3 500                       |
| electrical endurance (operating cycles) / at 480 V                                                                         | 5 100                       |
| electrical endurance (operating cycles) / at 600 V                                                                         | 3 500                       |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof                      | No                          |
| ground-fault monitoring version                                                                                            | without                     |
| product function                                                                                                           |                             |
| • communication function                                                                                                   | No                          |
| • other measurement function                                                                                               | No                          |
| Net Weight                                                                                                                 | 20.089 kg                   |
| Current                                                                                                                    |                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | Yes                         |
| operational current                                                                                                        |                             |
| • at 40 °C                                                                                                                 | 600 A                       |
| • at 45 °C                                                                                                                 | 600 A                       |
| • at 50 °C                                                                                                                 | 600 A                       |
| • at 55 °C                                                                                                                 | 600 A                       |
| • at 60 °C                                                                                                                 | 600 A                       |
| • at 65 °C                                                                                                                 | 555 A                       |
| • at 70 °C                                                                                                                 | 510 A                       |
| Switching capacity according to IEC 60947                                                                                  |                             |
| switching capacity class of the circuit breaker                                                                            | C                           |

|                                                                                                                   |                           |
|-------------------------------------------------------------------------------------------------------------------|---------------------------|
| maximum short-circuit current breaking capacity (Icu)                                                             |                           |
| • at 240 V                                                                                                        | 200 kA                    |
| • at 415 V                                                                                                        | 110 kA                    |
| • at 690 V                                                                                                        | 35 kA                     |
| operating short-circuit current breaking capacity (Ics)                                                           |                           |
| • at 240 V                                                                                                        | 150 kA                    |
| • at 415 V                                                                                                        | 85 kA                     |
| • at 690 V                                                                                                        | 19 kA                     |
| short-circuit current making capacity (Icm)                                                                       |                           |
| • at 240 V                                                                                                        | 440 kA                    |
| • at 415 V                                                                                                        | 242 kA                    |
| • at 690 V                                                                                                        | 74 kA                     |
| <b>Switching capacity according to UL 489</b>                                                                     |                           |
| current breaking capacity                                                                                         |                           |
| • at 240 V                                                                                                        | 200 kA                    |
| • at 480 V                                                                                                        | 100 kA                    |
| • at 600 V                                                                                                        | 50 kA                     |
| <b>Adjustable parameters</b>                                                                                      |                           |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic |                           |
| • minimum                                                                                                         | 250 A                     |
| • maximum                                                                                                         | 600 A                     |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic     |                           |
| • minimum                                                                                                         | 0.5 s                     |
| • maximum                                                                                                         | 17 s                      |
| adjustable response value setting current (I <sub>sd</sub> ) / of S-trip / with I <sub>0t</sub> characteristic    |                           |
| • minimum                                                                                                         | 900 A                     |
| • maximum                                                                                                         | 7 200 A                   |
| adjustable response value setting current (I <sub>sd</sub> ) / of S-trip / with I <sub>2t</sub> characteristic    |                           |
| • minimum                                                                                                         | 900 A                     |
| • maximum                                                                                                         | 7 200 A                   |
| adjustable response value delay time (t <sub>sd</sub> ) / for S-tripping / with I <sub>2t</sub> characteristic    |                           |
| • minimum                                                                                                         | 0.0001 s                  |
| • maximum                                                                                                         | 0.4 s                     |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping                                      |                           |
| • minimum                                                                                                         | 7 200 A                   |
| • maximum                                                                                                         | 7 200 A                   |
| adjustable response value delay time (t <sub>g</sub> ) / for G-tripping / with I <sub>0t</sub> characteristic     |                           |
| • minimum                                                                                                         | 0.1 s                     |
| • maximum                                                                                                         | 0.3 s                     |
| adjustable setting current (I <sub>nN</sub> ) / for N-tripping                                                    |                           |
| • minimum                                                                                                         | 300 A                     |
| • maximum                                                                                                         | 600 A                     |
| design of the N-conductor protection                                                                              | adjustable OFF; 50%; 100% |
| product function / grounding protection                                                                           | No                        |
| <b>Mechanical Design</b>                                                                                          |                           |
| product component                                                                                                 |                           |
| • undervoltage release                                                                                            | No                        |
| • voltage trigger                                                                                                 | No                        |
| • trip indicator                                                                                                  | No                        |
| height [in]                                                                                                       | 12.91 in                  |
| height                                                                                                            | 328 mm                    |
| width [in]                                                                                                        | 11.02 in                  |
| type of connectable conductor cross-sections / of the round conductor terminal / stranded                         | 2 x (4/0 - 600 kcmil)     |
| width                                                                                                             | 280 mm                    |

|                                                                 |                                           |
|-----------------------------------------------------------------|-------------------------------------------|
| depth [in]                                                      | 4.72 in                                   |
| depth                                                           | 120 mm                                    |
| <b>Connections</b>                                              |                                           |
| arrangement of electrical connectors / for main current circuit | Front connection                          |
| type of electrical connection / for main current circuit        | circular conductor terminal on both sides |
| <b>Auxiliary circuit</b>                                        |                                           |
| number of CO contacts / for auxiliary contacts                  | 0                                         |
| <b>Accessories</b>                                              |                                           |
| product extension / optional / motor drive                      | No                                        |
| <b>Environmental conditions</b>                                 |                                           |
| protection class IP / on the front                              | IP40                                      |
| ambient temperature                                             |                                           |
| • during operation / minimum                                    | -25 °C                                    |
| • during operation / maximum                                    | 70 °C                                     |
| • during storage / minimum                                      | -40 °C                                    |
| • during storage / maximum                                      | 80 °C                                     |
| reference code / according to IEC 81346-2                       | Q                                         |
| <b>Approvals / Certificates</b>                                 |                                           |
| General Product Approval                                        |                                           |
| EMV                                                             |                                           |



[Miscellaneous](#)



| Test Certificates                                  | Maritime application                                                                | other                        |                               | Dangerous goods                       | Environment                                 |
|----------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------|-------------------------------|---------------------------------------|---------------------------------------------|
| <a href="#">Type Test Certificates/Test Report</a> |  | <a href="#">Confirmation</a> | <a href="#">Miscellaneous</a> | <a href="#">Transport Information</a> | <a href="#">Environmental Confirmations</a> |

#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA6560-7HN46-2AA0>

##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA6560-7HN46-2AA0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)






[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA6560-7HN46-2AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA6560-7HN46-2AA0)

##### CAX-Online-Generator

<https://www.siemens.com/cax>

##### Tender specifications

<https://www.siemens.com/specifications>





last modified:

4/23/2025

