



circuit breaker 3VA6 UL frame 1200 breaking capacity class C 100kA @ 480 V 3-pole, line protection ETU350, LSI, In=1200A overload protection Ir=500A - 1200A short circuit protection Isd=1,5-10 x Ir, li=1,5 x In w/o connection

| Model                                                                                                                      |                             |
|----------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| product brand name                                                                                                         | SENTRON                     |
| product designation                                                                                                        | Molded-case circuit breaker |
| product designation / according to UL file                                                                                 | CNAE                        |
| design of the product                                                                                                      | System protection           |
| design of the load switch / according to UL 489 / Heating, Air Conditioning, and Refrigeration circuit breaker (HACR Type) | Yes                         |
| design of the overcurrent release                                                                                          | ETU350                      |
| protection function of the overcurrent release                                                                             | LSI                         |
| number of poles                                                                                                            | 3                           |
| General technical data                                                                                                     |                             |
| insulation voltage / rated value                                                                                           | 800 V                       |
| operating voltage / at AC / rated value                                                                                    | 600 V                       |
| power loss [W] / maximum                                                                                                   | 243 W                       |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole                                | 243 W                       |
| mechanical service life (operating cycles) / typical                                                                       | 3 000                       |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V                                                           | 1 500                       |
| electrical endurance (operating cycles) / at AC-1 / at 690 V                                                               | 500                         |
| electrical endurance (operating cycles) / at 480 V                                                                         | 1 500                       |
| electrical endurance (operating cycles) / at 600 V                                                                         | 500                         |
| product feature / for neutral conductors / upgradable/retrofitable / short-circuit and overload proof                      | No                          |
| ground-fault monitoring version                                                                                            | without                     |
| product function                                                                                                           |                             |
| • communication function                                                                                                   | No                          |
| • other measurement function                                                                                               | No                          |
| Net Weight                                                                                                                 | 25.7 kg                     |
| Current                                                                                                                    |                             |
| marking / according to UL 489 / 100%-rated breaker                                                                         | No                          |
| operational current                                                                                                        |                             |
| • at 40 °C                                                                                                                 | 1 200 A                     |
| • at 45 °C                                                                                                                 | 1 200 A                     |
| • at 50 °C                                                                                                                 | 1 200 A                     |
| • at 55 °C                                                                                                                 | 1 200 A                     |
| • at 60 °C                                                                                                                 | 1 200 A                     |
| • at 65 °C                                                                                                                 | 1 200 A                     |
| • at 70 °C                                                                                                                 | 1 200 A                     |
| Switching capacity according to IEC 60947                                                                                  |                             |
| switching capacity class of the circuit breaker                                                                            | C                           |

|                                                                                                                   |                   |
|-------------------------------------------------------------------------------------------------------------------|-------------------|
| maximum short-circuit current breaking capacity (I <sub>cu</sub> )                                                |                   |
| • at 240 V                                                                                                        | 200 kA            |
| • at 415 V                                                                                                        | 110 kA            |
| • at 690 V                                                                                                        | 35 kA             |
| operating short-circuit current breaking capacity (I <sub>cs</sub> )                                              |                   |
| • at 240 V                                                                                                        | 100 kA            |
| • at 415 V                                                                                                        | 55 kA             |
| • at 690 V                                                                                                        | 17 kA             |
| short-circuit current making capacity (I <sub>cm</sub> )                                                          |                   |
| • at 240 V                                                                                                        | 440 kA            |
| • at 415 V                                                                                                        | 242 kA            |
| • at 690 V                                                                                                        | 77 kA             |
| <b>Switching capacity according to UL 489</b>                                                                     |                   |
| current breaking capacity                                                                                         |                   |
| • at 240 V                                                                                                        | 200 kA            |
| • at 480 V                                                                                                        | 100 kA            |
| • at 600 V                                                                                                        | 65 kA             |
| <b>Adjustable parameters</b>                                                                                      |                   |
| adjustable response value setting current (I <sub>r</sub> ) / of the L-trip / with I <sub>2t</sub> characteristic |                   |
| • minimum                                                                                                         | 500 A             |
| • maximum                                                                                                         | 1 200 A           |
| adjustable response value delay time (t <sub>r</sub> ) / for L-tripping / with I <sub>2t</sub> characteristic     |                   |
| • minimum                                                                                                         | 2.5 s             |
| • maximum                                                                                                         | 30 s              |
| adjustable response value setting current (I <sub>sd</sub> ) / of S-trip / with I <sub>2t</sub> characteristic    |                   |
| • minimum                                                                                                         | 1 800 A           |
| • maximum                                                                                                         | 12 000 A          |
| adjustable response value delay time (t <sub>sd</sub> ) / for S-tripping / with I <sub>2t</sub> characteristic    |                   |
| • minimum                                                                                                         | 0.0001 s          |
| • maximum                                                                                                         | 0.4 s             |
| adjustable response value setting current (I <sub>i</sub> ) / for I-tripping                                      |                   |
| • minimum                                                                                                         | 12 000 A          |
| • maximum                                                                                                         | 12 000 A          |
| product function / grounding protection                                                                           | No                |
| <b>Mechanical Design</b>                                                                                          |                   |
| product component                                                                                                 |                   |
| • undervoltage release                                                                                            | No                |
| • trip indicator                                                                                                  | No                |
| height [in]                                                                                                       | 8.14 in           |
| height                                                                                                            | 206.9 mm          |
| width [in]                                                                                                        | 8.99 in           |
| width                                                                                                             | 228.4 mm          |
| depth [in]                                                                                                        | 16 in             |
| depth                                                                                                             | 406.4 mm          |
| <b>Connections</b>                                                                                                |                   |
| type of electrical connection / for main current circuit                                                          | without terminals |
| design of the surface / of the connections / on the top of the switch (N, 1, 3, 5)                                | silver            |
| design of the surface / of the connections / on the bottom of the switch (N, 2, 4, 6)                             | silver            |
| <b>Auxiliary circuit</b>                                                                                          |                   |
| number of CO contacts / for auxiliary contacts                                                                    | 0                 |
| <b>Environmental conditions</b>                                                                                   |                   |
| protection class IP / on the front                                                                                | IP40              |
| ambient temperature                                                                                               |                   |
| • during operation / minimum                                                                                      | -25 °C            |

- during operation / maximum 70 °C
- during storage / minimum -40 °C
- during storage / maximum 80 °C

reference code / according to IEC 81346-2

F

## Approvals / Certificates

### General Product Approval



### General Product Approval

### EMV

### Test Certificates

### Maritime application

### other

[Miscellaneous](#)



[Type Test Certificates/Test Report](#)



[Confirmation](#)

### other

### Dangerous goods

### Environment

[Miscellaneous](#)

[Transport Information](#)

[Environmental Confirmations](#)

## Further information

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA6712-7HN31-0AA0>

### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA6712-7HN31-0AA0>

### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)



[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA6712-7HN31-0AA0](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA6712-7HN31-0AA0)


### CAX-Online-Generator

<https://www.siemens.com/cax>

### Tender specifications

<https://www.siemens.com/specifications>





last modified:

3/31/2025

