SIEMENS

Data sheet 5SU1324-6KX16



Figure similar

RCBO, Icn: 10 kA, 2P, type A, 30 mA, B char., In: 16 A, Un AC: 110 V

Model	
product brand name	SENTRON
product designation	RCBO
design of the product	Instantaneous
General technical data	
number of poles	2
number of poles with protection	2
design of pole	2P
tripping characteristic class	B
mechanical service life (operating cycles) typical	10 000
overvoltage category	3
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui) rated value	264 V
surge voltage resistance rated value	4 000 V
surge current resistance at (8/20) µs	1 kA
tripping fault current rated value	30 mA
• operational current	
— at 30 °C rated value	16 A
— at 40 °C rated value	15.2 A
— at 45 °C rated value	14.88 A
— at 50 °C rated value	14.4 A
— at 55 °C rated value	13.92 A
— at 60 °C rated value	13.6 A
— at 65 °C rated value	12.96 A
— at 70 °C rated value	12.32 A
• operational current at AC rated value	16 A
residual current type	A
Supply voltage	
supply voltage	
• at AC rated value	110/120 V
• for testing equipment minimum	100 V
operating frequency	50/60 Hz
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors

Subject to change without notice
© Copyright Siemens

Breaking Capacity	
switching capacity current	
● according to EN 60898 rated value	10 kA
● according to IEC 60947-2 rated value	20 kA
short-circuit current breaking capacity (Icn) according to EN 61009-1 rated value	10 kA
rated residual switching capacity (IΔm) according to IEC 61009-1	10 kA
energy limitation class	3
Dissipation	
power loss [W]	
● maximum	4.9 W
Product details	
product feature touch protection	Yes
product component neutral conductor switching	Yes
product feature halogen-free	Yes
product feature silicon-free	Yes
Connections	
connectable conductor cross-section solid	
● minimum	0.75 mm²
● maximum	35 mm²
connectable conductor cross-section stranded	
● minimum	0.75 mm²
● maximum	35 mm²
connectable conductor cross-section finely stranded with core end processing	
● minimum	0.75 mm²
● maximum	25 mm²
tightening torque with screw-type terminals	
● minimum	2.5 N·m
● maximum	3 N·m
position of power supply cord	Either top or bottom
Mechanical Design	
height	90 mm
width	54 mm
depth	77 mm
installation depth	70 mm
number of modular width units	3
mounting position	any
Net Weight	407 g
weight with packaging	408 g
Environmental conditions	
influence of the surrounding temperature	Max. 95% humidity
ambient temperature during operation	
● minimum	-25 °C
● maximum	55 °C
ambient temperature during storage	
● minimum	-40 °C
● maximum	75 °C
number of test cycles for environmental testing according to IEC 60068-2-30	28

Approvals Certificates

General Product Approval			Test Certificates
Confirmation	Miscellaneous		Special Test Certific-ate

other	Railway


Subject to change without notice
© Copyright Siemens

产品合格 QC PASS	Confirmation	Miscellaneous	Miscellaneous	Special Test Certific-ate	Confirmation

Dangerous goods	Environment	
Transport Information	Environmental Con-firmations	Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1324-6KX16
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SU1324-6KX16
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1324-6KX16
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications



last modified: 7/22/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens