SIEMENS

Data sheet 5SU1326-6FP20



RCBO, 6 kA, 2P Type A, 30 mA, B-Char, In: 20A Un: 230V

Model	
product brand name	SENTRON
product designation	RCBO
design of the product	Instantaneous
General technical data	
number of poles	2
number of poles with protection	2
design of pole	2P
tripping characteristic class	B
mechanical service life (operating cycles) typical	10 000
overvoltage category	3
degree of pollution	3
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui) rated value	500 V
surge voltage resistance rated value	4 000 V
surge current resistance at (8/20) µs	0.25 kA
tripping fault current rated value	30 mA
● operational current	
— at 30 °C rated value	20 A
— at 40 °C rated value	19.5 A
— at 45 °C rated value	19.2 A
— at 50 °C rated value	18.9 A
— at 55 °C rated value	18.7 A
— at 60 °C rated value	18.4 A
— at 70 °C rated value	17.8 A
● operational current at AC rated value	20 A
residual current type	A
Supply voltage	
supply voltage	
● at AC rated value	230/240 V
● for testing equipment minimum	195 V
operating frequency	50 Hz
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Breaking Capacity	
switching capacity current	

Subject to change without notice
© Copyright Siemens

● according to EN 60898 rated value	6 kA
● according to IEC 60947-2 rated value	7.5 kA
short-circuit current breaking capacity (Icn) according to EN 61009-1 rated value	6 kA
rated residual switching capacity (IΔm) according to IEC 61009-1	4.5 kA
energy limitation class	3
Dissipation	
power loss [W]	
● for rated value of the current at AC in hot operating state per pole	1.36 W
● maximum	2.7 W
Product details	
product feature touch protection	Yes
product component neutral conductor switching	Yes
product feature halogen-free	No
Connections	
connectable conductor cross-section solid	
● minimum	1 mm²
● maximum	35 mm²
connectable conductor cross-section stranded	
● minimum	1 mm²
● maximum	35 mm²
connectable conductor cross-section finely stranded with core end processing	
● minimum	1 mm²
● maximum	35 mm²
tightening torque with screw-type terminals	
● minimum	2 N·m
● maximum	2 N·m
position of power supply cord	Either top or bottom
Mechanical Design	
height	85 mm
width	36 mm
depth	72 mm
installation depth	70 mm
number of modular width units	2
mounting position	any
Net Weight	246 g
weight with packaging	282 g
Environmental conditions	
influence of the surrounding temperature	Max. 95% humidity
ambient temperature during operation	
● minimum	-25 °C
● maximum	40 °C
ambient temperature during storage	
● minimum	-40 °C
● maximum	70 °C
number of test cycles for environmental testing according to IEC 60068-2-30	28

Approvals Certificates


General Product Approval				other	
UKCA	CE EG-Konf.	Miscellaneous	EAC	Confirmation	产品合格 QC PASS


other	Dangerous goods	Environment

© Copyright Siemens

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1326-6FP20
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SU1326-6FP20
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1326-6FP20
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications





Subject to change without notice
© Copyright Siemens

last modified:	7/22/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens