SIEMENS

Data sheet 5SU1346-7FP16



RCBO, 6 kA, 4P Type A, 30 mA, C-Char, In: 16A Un: 400V

Model	
product brand name	SENTRON
product designation	RCBO
design of the product	Instantaneous
General technical data	
number of poles	4
number of poles with protection	4
design of pole	4P
tripping characteristic class	C
mechanical service life (operating cycles) typical	10 000
overvoltage category	3
degree of pollution	3
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui) rated value	500 V
surge voltage resistance rated value	4 000 V
surge current resistance at (8/20) µs	0.25 kA
tripping fault current rated value	30 mA
● operational current	
— at 30 °C rated value	16 A
— at 40 °C rated value	15.2 A
— at 45 °C rated value	14.8 A
— at 50 °C rated value	14.3 A
— at 55 °C rated value	13.9 A
— at 60 °C rated value	13.4 A
— at 70 °C rated value	12.5 A
● operational current at AC rated value	16 A
residual current type	A
Supply voltage	
supply voltage	
● at AC rated value	400 V
● for testing equipment minimum	195 V
operating frequency	50 Hz
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20, if the distribution board is installed, with connected conductors
Breaking Capacity	
switching capacity current	

Subject to change without notice
© Copyright Siemens

● according to EN 60898 rated value	6 kA
● according to IEC 60947-2 rated value	6 kA
short-circuit current breaking capacity (Icn) according to EN 61009-1 rated value	6 kA
rated residual switching capacity (IΔm) according to IEC 61009-1	4.5 kA
energy limitation class	3
Dissipation	
power loss [W]	
● maximum	2.3 W
Product details	
product feature touch protection	Yes
product component neutral conductor switching	Yes
product feature halogen-free	No
Connections	
connectable conductor cross-section solid	
● minimum	1 mm²
● maximum	35 mm²
connectable conductor cross-section stranded	
● minimum	1 mm²
● maximum	35 mm²
connectable conductor cross-section finely stranded with core end processing	
● minimum	1 mm²
● maximum	35 mm²
tightening torque with screw-type terminals	
● minimum	2 N·m
● maximum	2 N·m
position of power supply cord	Either top or bottom
Mechanical Design	
height	85 mm
width	72 mm
depth	72 mm
installation depth	70 mm
number of modular width units	4
mounting position	any
Net Weight	471 g
weight with packaging	496 g
Environmental conditions	
influence of the surrounding temperature	Max. 95% humidity
ambient temperature during operation	
● minimum	-25 °C
● maximum	40 °C
ambient temperature during storage	
● minimum	-40 °C
● maximum	70 °C
number of test cycles for environmental testing according to IEC 60068-2-30	28
Environmental footprint	
Environmental Product Declaration(EPD)	Yes
global warming potential [CO2 eq] total	13.9 kg
global warming potential [CO2 eq] during manufacturing	3.2 kg
global warming potential [CO2 eq] during operation	10.8 kg
global warming potential [CO2 eq] after end of life	-0.161 kg
Approvals Certificates	
General Product Approval	

© Copyright Siemens

		Confirmation		Miscellaneous	


other				Dangerous goods	Environment
Confirmation		Miscellaneous	Miscellaneous	Transport Information	

Environment	
Environmental Con-firmations	Environmental Con-firmations

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SU1346-7FP16
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5SU1346-7FP16
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SU1346-7FP16
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications

Subject to change without notice
© Copyright Siemens



last modified: 7/22/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens