SIEMENS

Data sheet 5TC1272



DELTA, shutter/blind control

Model	
product brand name	DELTA
product designation	Shutter/blind control
Supply voltage	
operating voltage rated value	230 V
supply voltage frequency	
● minimum	50 Hz
● maximum	60 Hz
Breaking Capacity	
switching capacity current	5 A
Main circuit	
operational current rated value	5 A
Relay contacts	
switching voltage of relay contacts rated value	250 V
Product details	
product component extension input	No
Number	
number of motors connectable	1
Connections	
type of electrical connection	Max. 2.5 mm²
Mechanical Design	
width	47.5 mm
depth	20 mm
length	47.5 mm
fastening method	screw fixing
Net Weight	53 g
Environmental conditions	
ambient temperature during operation	
● minimum	-10 °C
● maximum	55 °C
Approvals Certificates	

General Product Approval	other	Environment
CE EG-Konf.	Miscellaneous	EAC Confirmation	Environmental Confirmations

Subject to change without notice
© Copyright Siemens

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TC1272
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/5TC1272
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TC1272
CAx-Online-Generator
https://www.siemens.com/cax
Tender specifications
https://www.siemens.com/specifications

last modified: 5/26/2025

© Copyright Siemens

Subject to change without notice
© Copyright Siemens