SIEMENS

Data sheet 6AG1331-7KF02-2AB0



Figure similar

spare part SIPLUS S7-300 SM 331 20-pole based on 6ES7331-7KF02-0AB0 with conformal coating, -25…+70 °C, analog input isolated 8 AI, resolution 9/12/14 bits, U/I/thermocouple/resistor, alarm, diagnostics, 1x 20-pole removing/inserting with active backplane bus

General information	
based on	6ES7331-7KF02-0AB0
Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V; A power supply according to EN 50155 shall be used for railway applications
● Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	200 mA
from backplane bus 5 V DC, max.	50 mA
Power loss	
Power loss, typ.	1 W
Analog inputs	
Number of analog inputs	8
● For resistance measurement	4
permissible input voltage for voltage input (destruction limit), max.	20 V; continuous; 75 V for max. 1 s (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
● Voltage	Yes
● Current	Yes
● Thermocouple	Yes
● Resistance thermometer	Yes
● Resistance	Yes
Input ranges (rated values), voltages	
● 0 to +10 V	No
● 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	100 kΩ
● 1 V to 10 V	No
● -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
● -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	100 kΩ
● -250 mV to +250 mV	Yes
— Input resistance (-250 mV to +250 mV)	10 MΩ

Subject to change without notice
© Copyright Siemens

● -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	100 kΩ
● -50 mV to +50 mV	No
● -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	10 MΩ
● -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	25 Ω
● -10 mA to +10 mA	Yes
— Input resistance (-10 mA to +10 mA)	25 Ω
● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	25 Ω
● -3.2 mA to +3.2 mA	Yes
— Input resistance (-3.2 mA to +3.2 mA)	25 Ω
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	25 Ω
Input ranges (rated values), thermocouples	
● Type B	No
● Type C	No
● Type E	Yes
— Input resistance (Type E)	10 MΩ
● Type J	Yes
— Input resistance (type J)	10 MΩ
● Type K	Yes
— Input resistance (Type K)	10 MΩ
● Type L	No
● Type N	Yes
— Input resistance (Type N)	10 MΩ
● Type R	No
● Type S	No
● Type T	No
● Type U	No
● Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
● Cu 10	No
● Ni 100	Yes; Standard
— Input resistance (Ni 100)	10 MΩ
● Ni 1000	No
● LG-Ni 1000	No
● Ni 120	No
● Ni 200	No
● Ni 500	No
● Pt 100	Yes; Standard
— Input resistance (Pt 100)	10 MΩ
● Pt 1000	No
● Pt 200	No
● Pt 500	No
Input ranges (rated values), resistors	
● 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
● 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
● 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
● 0 to 6000 ohms	No
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— internal temperature compensation	Yes

© Copyright Siemens

— external temperature compensation with compensations socket	Yes
— for definable comparison point temperature	Yes
Characteristic linearization	
● parameterizable	Yes
— for thermocouples	Type E, J, K, L, N
— for resistance thermometer	Pt100 (standard, climatic range), Ni100 (standard, climatic range)
Cable length	
● shielded, max.	200 m; 50 m at 80 mV and thermocouples
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	15 bit; Unipolar: 9/12/12/14 bit; bipolar: 9 bit + sign/12 bit + sign/12 bit + sign/14 bit + sign
● Integration time, parameterizable	Yes; 2,5 / 16,67 / 20 / 100 ms
● Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10 Hz
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
● for current measurement as 2-wire transducer	Yes
● for current measurement as 4-wire transducer	Yes
● for resistance measurement with two-wire connection	Yes
● for resistance measurement with three-wire connection	Yes
● for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	1 %; ±1% (80 mV); ±0.6% (250 mV to 1 000 mV); ±0.8% (2.5 V to 10 V) @ 0 ... +60 °C; ±1.3% (80 mV); ±0.8% (250 mV to 1 000 mV); ±1% (2.5 V to 10 V) @ -25 ... +70 °C
● Current, relative to input range, (+/-)	0.7 %; @ 0 ... +60 °C; ±0.9% @ -25 ... +70 °C; from 3.2 mA to 20 mA
● Resistance, relative to input range, (+/-)	0.7 %; @ 0 ... +60 °C; ±0.9% @ -25 ... +70 °C; 150, 300, 600 ohm
● Resistance thermometer, relative to input range, (+/-)	0.7 %; ±0.7 % (Pt100 / Ni100); ±0.8 % (Pt100 climate) @ 0 ... +60 °C; ±0.9 % (Pt100 / Ni100); ±1 % (Pt100 climate) @ -25 ... +70 °C
● Thermocouple, relative to input range, (+/-)	1.1 %; @ 0 ... +60 °C; ±1.3% @ -25 ... +70 °C; type E, J, K, L, N
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.6 %; ±0.4 % (250 mV to 1 000 mV); ±0.6 % (2.5 mV to 10 mV); ±0.7 % (80 mV)
● Current, relative to input range, (+/-)	0.5 %; 3.2 to 20 mA
● Resistance, relative to input range, (+/-)	0.5 %; 150, 300, 600 Ohm
● Resistance thermometer, relative to input range, (+/-)	0.6 %; ±0.5% (Pt100/ Ni100), ±0.6% (Pt100 climate)
● Thermocouple, relative to input range, (+/-)	0.7 %; Type E, N, J, K, L
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
● Diagnostic alarm	Yes; Parameterizable, channels 0 and 2
● Limit value alarm	Yes; Parameterizable
Diagnoses	
● Diagnostic information readable	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
● between the channels	No
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	500 V DC
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes

Subject to change without notice
© Copyright Siemens

EAC (formerly Gost-R)	Yes
Railway application	
● EN 50155	Yes; Sections 4, 5 and 12; no further agreements apply; T1, Category 1, Class A/B, EN 50155:2007 (see SIOS entry 109755985)
Ambient conditions	
Ambient temperature during operation	
● min.	-25 °C; = Tmin
● max.	70 °C; = Tmax; for use on railway vehicles according to EN50155, the rated temperature range -25 ... +55 °C (T1) or 60 °C @ UL/ULhaz/ATEX/FM use applies
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on land craft, rail vehicles and special-purpose vehicles	
— to biologically active substances according to EN 60721-3-5	Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request
— to chemically active substances according to EN 60721-3-5	Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 50155 (ST2); *
— to mechanically active substances according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust; *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	250 g
Classifications	

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01

Subject to change without notice
© Copyright Siemens

eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Manufacturer Declaration

Declaration of Conformity

China RoHS

EMV

For use in hazardous locations

CCC-Ex

last modified: 12/8/2024

Subject to change without notice
© Copyright Siemens