SIEMENS

Data sheet 6AG1443-1GX30-4XE0

product type designation	**CP 443-1 Advanced**
	SIPLUS NET CP 443-1 Advanced based on 6GK7443-1GX30-0XE0 with conformal coating, 0…+60 °C, 1x 10/100/1000 Mbps; 4x 10/100 Mbps (IE switch); RJ 45 ports; ISO; TCP; UDP; PROFINET IO controller S7 communication; open communication (send/ receive); S7 routing; IP configuration via DHCP/block; IP access control list; time- -of-day synchronization; extended Web diagnostics; fast start up; support for PROFIenergy; IP routing; FTP; web server;



Figure similar

Technical Product Detail Page	https://i.siemens.com/1P6AG1443-1GX30-4XE0
transfer rate	
transfer rate	
● at the 1st interface	10 ... 1000 Mbit/s
● at the 2nd interface	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	5
number of electrical connections	
● at the 1st interface / according to Industrial Ethernet	1
● at the 2nd interface / according to Industrial Ethernet	4
type of electrical connection	
● at the 1st interface / according to Industrial Ethernet	RJ45 port
● at the 2nd interface / according to Industrial Ethernet	RJ45 port
design of the removable storage	
● C-PLUG	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
relative symmetrical tolerance / at DC	
● at 5 V	5 %
consumed current	
● from backplane bus / at DC / at 5 V / typical	1.8 A
power loss [W]	9 W
ambient conditions	
ambient temperature	
● during operation	0 ... 60 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity	
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	

Subject to change without notice
© Copyright Siemens

● conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
● conformity according to EN 60721-3-6	Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes
resistance to mechanically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
● conformity according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.7 kg
product features, product functions, product components / general	
number of units	
● per CPU / maximum	14
● note	max. 4 as PN IO ctrl.
performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
data volume	
● as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
● as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
● as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum	8 Kibyte
● as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum	2 Kibyte
number of possible connections / for open communication	
● by means of T blocks / maximum	64
data volume	
● as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum	1452 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
● maximum	128; when using several CPUs
● with PG connections / maximum	2
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	128
performance data / IT functions	
number of possible connections	
● as client / by means of FTP / maximum	20
● as server / by means of FTP / maximum	10
number of possible connections	

© Copyright Siemens

● as server / by means of HTTP / maximum	4
● as email client / maximum	1
data volume / as user data for email / maximum	8 Kibyte
storage capacity / of the user memory	
● as flash memory file system	30 Mibyte
● as RAM	16 Mibyte
● additionally buffered as RAM via central backup battery	512 Kibyte
number of possible write cycles / of the flash memory cells	100000
performance data / PROFINET communication / as PN IO controller	
product function / PROFINET IO controller	Yes
number of PN IO devices / on PROFINET IO controller / operable / total	128
number of PN IO IRT devices / on PROFINET IO controller / operable	64
number of external PN IO lines / with PROFINET / per rack	4
data volume	
● as user data for input variables / as PROFINET IO controller / maximum	8 Kibyte
● as user data for output variables / as PROFINET IO controller / maximum	8 Kibyte
● as user data for input variables per PN IO device / as PROFINET IO controller / maximum	1433 byte
● as user data for output variables per PN IO device / as PROFINET IO controller / maximum	1433 byte
● as user data for input variables per PN IO device / for each sub-module as PROFINET IO controller / maximum	240 byte
● as user data for output variables per PN IO device / for each sub-module as PROFINET IO controller / maximum	240 byte
performance data / telecontrol	
protocol / is supported	
● TCP/IP	Yes
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
● SNMP v1	Yes
● SNMP v3	Yes
● DCP	Yes
● LLDP	Yes
configuration software	
● required	STEP 7 V5.5 SP3 or higher / STEP 7 Professional V12 (TIA Portal) or higher
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / switch	
product feature / switch	Yes
product function	
● switch-managed	No
● with IRT / PROFINET IO switch	Yes
● configuration with STEP 7	Yes
product functions / redundancy	
product function	
● ring redundancy	Yes
● redundancy manager	Yes
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product functions / security	
firewall version	stateful inspection
product function / with VPN connection	IPSec
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1
number of possible connections / with VPN connection	32

© Copyright Siemens

product function	
● password protection for Web applications	Yes
● ACL - IP-based	Yes
● ACL - IP-based for PLC/routing	Yes
● switch-off of non-required services	Yes
● blocking of communication via physical ports	Yes
● log file for unauthorized access	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
● NTP	Yes
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval				EMV	
CE EG-Konf.	Manufacturer Declaration	UKCA	China RoHS	KC	RCM

For use in hazardous locations

CCC-Ex	Ex ATEX	IECEx IECEx

last modified: 10/28/2025

Subject to change without notice
© Copyright Siemens