SIEMENS

Data sheet 6AG1531-7KF00-7AB0



Figure similar

SIPLUS S7-1500 AI 8xU/I/RTD/TC based on 6ES7531-7KF00-0AB0 with conformal coating, -40…+70 °C, analog input module 16-bit resolution, accuracy 0.3%, 8 channels in groups of 8, 4 channels for RTD measurement, common mode voltage 10 V; diagnostics; hardware interrupts including infeed element, shielding bracket and shield terminal

General information	
Product type designation	AI 8xU/I/RTD/TC ST
Firmware version	
● FW update possible	Yes
based on	6ES7531-7KF00-0AB0
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
● Prioritized startup	No
● Measuring range scalable	No
● Scalable measured values	No
● Adjustment of measuring range	No
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	see entry ID: 109746275
Operating mode	
● Oversampling	No
● MSI	Yes
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	255 mA; with 19.2 V supply
Encoder supply	
24 V encoder supply	
● Short-circuit protection	Yes
● Output current, max.	20 mA; Max. 47 mA per channel for a duration < 10 s
Power	
Power consumption from the backplane bus	0.7 W
Power loss	
Power loss, typ.	2.7 W
Analog inputs	
Number of analog inputs	8; > +60 °C max. 2x ±20 mA or 4x ±10 V or 4x RTD permissible
● For current measurement	8
● For voltage measurement	8

Subject to change without notice
© Copyright Siemens

● For resistance/resistance thermometer measurement	4
● For thermocouple measurement	8
permissible input voltage for voltage input (destruction limit), max.	28.8 V
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	150 Ohm, 300 Ohm, 600 Ohm, Pt100, Pt200, Ni100: 1.25 mA; 6 000 Ohm, Pt500, Pt1000, Ni1000, LG-Ni1000: 0.625 mA; PTC: 0.472 mA
Technical unit for temperature measurement adjustable	Yes; °C/°F/K
Input ranges (rated values), voltages	
● 0 to +5 V	No
● 0 to +10 V	No
● 1 V to 5 V	Yes
— Input resistance (1 V to 5 V)	100 kΩ
● -1 V to +1 V	Yes
— Input resistance (-1 V to +1 V)	10 MΩ
● -10 V to +10 V	Yes
— Input resistance (-10 V to +10 V)	100 kΩ
● -2.5 V to +2.5 V	Yes
— Input resistance (-2.5 V to +2.5 V)	10 MΩ
● -25 mV to +25 mV	No
● -250 mV to +250 mV	Yes
— Input resistance (-250 mV to +250 mV)	10 MΩ
● -5 V to +5 V	Yes
— Input resistance (-5 V to +5 V)	100 kΩ
● -50 mV to +50 mV	Yes
— Input resistance (-50 mV to +50 mV)	10 MΩ
● -500 mV to +500 mV	Yes
— Input resistance (-500 mV to +500 mV)	10 MΩ
● -80 mV to +80 mV	Yes
— Input resistance (-80 mV to +80 mV)	10 MΩ
Input ranges (rated values), currents	
● 0 to 20 mA	Yes
— Input resistance (0 to 20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
● -20 mA to +20 mA	Yes
— Input resistance (-20 mA to +20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
● 4 mA to 20 mA	Yes
— Input resistance (4 mA to 20 mA)	25 Ω; Plus approx. 42 ohms for overvoltage protection by PTC
Input ranges (rated values), thermocouples	
● Type B	Yes
— Input resistance (Type B)	10 MΩ
● Type C	No
● Type E	Yes
— Input resistance (Type E)	10 MΩ
● Type J	Yes
— Input resistance (type J)	10 MΩ
● Type K	Yes
— Input resistance (Type K)	10 MΩ
● Type L	No
● Type N	Yes
— Input resistance (Type N)	10 MΩ
● Type R	Yes
— Input resistance (Type R)	10 MΩ
● Type S	Yes
— Input resistance (Type S)	10 MΩ
● Type T	Yes
— Input resistance (Type T)	10 MΩ
● Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
● Cu 10	No
● Cu 10 according to GOST	No
● Cu 50	No

Subject to change without notice
© Copyright Siemens

● Cu 50 according to GOST	No
● Cu 100	No
● Cu 100 according to GOST	No
● Ni 10	No
● Ni 10 according to GOST	No
● Ni 100	Yes; Standard/climate
— Input resistance (Ni 100)	10 MΩ
● Ni 100 according to GOST	No
● Ni 1000	Yes; Standard/climate
— Input resistance (Ni 1000)	10 MΩ
● Ni 1000 according to GOST	No
● LG-Ni 1000	Yes; Standard/climate
— Input resistance (LG-Ni 1000)	10 MΩ
● Ni 120	No
● Ni 120 according to GOST	No
● Ni 200 according to GOST	No
● Ni 500	No
● Ni 500 according to GOST	No
● Pt 10	No
● Pt 10 according to GOST	No
● Pt 50	No
● Pt 50 according to GOST	No
● Pt 100	Yes; Standard/climate
— Input resistance (Pt 100)	10 MΩ
● Pt 100 according to GOST	No
● Pt 1000	Yes; Standard/climate
— Input resistance (Pt 1000)	10 MΩ
● Pt 1000 according to GOST	No
● Pt 200	Yes; Standard/climate
— Input resistance (Pt 200)	10 MΩ
● Pt 200 according to GOST	No
● Pt 500	Yes; Standard/climate
— Input resistance (Pt 500)	10 MΩ
● Pt 500 according to GOST	No
Input ranges (rated values), resistors	
● 0 to 150 ohms	Yes
— Input resistance (0 to 150 ohms)	10 MΩ
● 0 to 300 ohms	Yes
— Input resistance (0 to 300 ohms)	10 MΩ
● 0 to 600 ohms	Yes
— Input resistance (0 to 600 ohms)	10 MΩ
● 0 to 3000 ohms	No
● 0 to 6000 ohms	Yes
— Input resistance (0 to 6000 ohms)	10 MΩ
● PTC	Yes
— Input resistance (PTC)	10 MΩ
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— internal temperature compensation	Yes
— external temperature compensation via RTD	Yes
— Compensation for 0 °C reference point temperature	Yes; fixed value can be set
— Reference channel of the module	Yes
Cable length	
● shielded, max.	800 m; for U/I, 200 m for R/RTD, 50 m for TC
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Integration time, parameterizable	Yes
● Integration time (ms)	2,5 / 16,67 / 20 / 100 ms
● Basic conversion time, including integration time (ms)	9 / 23 / 27 / 107 ms

Subject to change without notice
© Copyright Siemens

— additional conversion time for wire-break monitoring	9 ms (to be considered in R/RTD/TC measurement)
— additional conversion time for resistance measurement	150 ohm, 300 ohm, 600 ohm, Pt100, Pt200, Ni100: 2 ms, 6000 ohm, Pt500, Pt1000, Ni1000, LG-Ni1000, PTC: 4 ms
● Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 / 10 Hz
● Time for offset calibration (per module)	Basic conversion time of the slowest channel
Smoothing of measured values	
● parameterizable	Yes
● Step: None	Yes
● Step: low	Yes
● Step: Medium	Yes
● Step: High	Yes
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes
● for current measurement as 2-wire transducer	Yes
— Burden of 2-wire transmitter, max.	820 Ω
● for current measurement as 4-wire transducer	Yes
● for resistance measurement with two-wire connection	Yes; Only for PTC
● for resistance measurement with three-wire connection	Yes; All measuring ranges except PTC; internal compensation of the cable resistances
● for resistance measurement with four-wire connection	Yes; All measuring ranges except PTC
Errors/accuracies	
Linearity error (relative to input range), (+/-)	0.02 %
Temperature error (relative to input range), (+/-)	0.005 %/K; With TC type T 0.02 ± % / K
Crosstalk between the inputs, max.	-80 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.02 %
Temperature error of internal compensation	±6 °C
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.4 %
● Current, relative to input range, (+/-)	0.4 %
● Resistance, relative to input range, (+/-)	0.4 %
● Resistance thermometer, relative to input range, (+/-)	Ptxxx standard: ±1.5 K, Ptxxx climate: ±0.5 K, Nixxx standard: ±0.5 K, Nixxx climate: ±0.3 K
● Thermocouple, relative to input range, (+/-)	Type B: > 600 °C ±4.6 K, type E: > -200 °C ±1.5 K, type J: > -210 °C ±1.9 K, type K: > -200 °C ±2.4 K, type N: > -200 °C ±2.9 K, type R: > 0 °C ±4.7 K, type S: > 0 °C ±4.6 K, type T: > -200 °C ±2.4 K
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.1 %
● Current, relative to input range, (+/-)	0.1 %
● Resistance, relative to input range, (+/-)	0.1 %
● Resistance thermometer, relative to input range, (+/-)	Ptxxx standard: ±0.7 K, Ptxxx climate: ±0.2 K, Nixxx standard: ±0.3 K, Nixxx climate: ±0.15 K
● Thermocouple, relative to input range, (+/-)	Type B: > 600 °C ±1.7 K, type E: > -200 °C ±0.7 K, type J: > -210 °C ±0.8 K, type K: > -200 °C ±1.2 K, type N: > -200 °C ±1.2 K, type R: > 0 °C ±1.9 K, type S: > 0 °C ±1.9 K, type T: > -200 °C ±0.8 K
Interference voltage suppression for f = n x (f1 +/- 1 %), f1 = interference frequency	
● Series mode interference (peak value of interference < rated value of input range), min.	40 dB
● Common mode voltage, max.	10 V
● Common mode interference, min.	60 dB
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
● Diagnostic alarm	Yes
● Limit value alarm	Yes; two upper and two lower limit values in each case
Diagnoses	
● Monitoring the supply voltage	Yes
● Wire-break	Yes; Only for 1 to 5 V, 4 to 20 mA, TC, R, and RTD
● Overflow/underflow	Yes
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED

Subject to change without notice
© Copyright Siemens

● Monitoring of the supply voltage (PWR-LED)	Yes; green LED
● Channel status display	Yes; green LED
● for channel diagnostics	Yes; red LED
● for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels, in groups of	8
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Permissible potential difference	
between the inputs (UCM)	20 V DC
Between the inputs and MANA (UCM)	10 V DC
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for applications according to AMS 2750	Yes; Declaration of Conformity, see online support entry 109757262
Suitable for applications according to CQI-9	Yes; Based on AMS 2750 E
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	38.6 kg
— global warming potential, (during production) [CO2 eq]	14.4 kg
— global warming potential, (during operation) [CO2 eq]	24.6 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.44 kg
product functions / security / header	
signed firmware update	No
data integrity	No
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost)
● horizontal installation, max.	70 °C; = Tmax
● vertical installation, min.	-40 °C; = Tmin
● vertical installation, max.	40 °C; = Tmax
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m
● Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
● With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	

© Copyright Siemens

— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
● Coatings for printed circuit board assemblies acc. to EN 61086	Yes; Class 2 for high reliability
● Protection against fouling acc. to EN 60664-3	Yes; Type 1 protection
● Military testing according to MIL-I-46058C, Amendment 7	Yes; Discoloration of coating possible during service life
● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, Class A
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	310 g
Other	
Note:	Additional basic error and noise for integration time = 2.5 ms: Voltage: ±250 mV (±0.02%), ±80 mV (±0.05%), ±50 mV (±0.05%); resistance: 150 ohms ±0.02%; resistance thermometer: Pt100 climate: ±0.08 K, Ni100 climate: ±0.08 K; thermocouple: Type B, R, S: ±3 K, type E, J, K, N, T: ±1 K

Classifications

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

EG-Konf. UKCA China RoHS Manufacturer Declaration UL

EMV

KC

EMV

RCM

For use in hazardous locations

IECEx ATEX

Maritime application

DNV

Environment

EPD

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens