SIEMENS

## Data sheet 6AG2193-6AR00-4AA0



Figure similar

SIPLUS ET 200SP BA 2xRJ45 TX rail based on 6ES7193-6AR00-0AA0 with conformal coating, -40…+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), BusAdapter 2x RJ45 sockets for PROFINET

| | |
|---|---|
| **General information** | |
| Product type designation | BA 2x RJ45 |
| based on | 6ES7193-6AR00-0AA0 |
| **Interfaces** | |
| Number of PROFINET interfaces | 1; 2 ports (switch) 2x RJ45 |
| Supports protocol for PROFINET IO | |
| ● Number of RJ45 ports | 2 |
| Cable length | |
| — Cu conductors | 100 m |
| **Standards, approvals, certificates** | |
| Ecological footprint | |
| ● environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO2 eq] | 1.14 kg |
| — global warming potential, (during production) [CO2 eq] | 1.2 kg |
| — global warming potential, (during operation) [CO2 eq] | 0 kg |
| — global warming potential, (after end of life cycle) [CO2 eq] | -0.069 kg |
| Railway application | |
| ● EN 50121-3-2 | Yes; EMC for rail vehicles |
| ● EN 50121-4 | Yes; EMC for signal and telecommunications systems |
| ● EN 50121-5 | Yes; EMC for fixed installations and railway power supply equipment |
| ● EN 50124-1 | Yes; Railway applications - overvoltage category OV2; pollution degree PD2; rated surge voltage UNi = 0.5 kV; UNm = 24 V DC |
| ● EN 50125-1 | Yes; Rail vehicles - see ambient conditions |
| ● EN 50125-2 | Yes; Stationary electrical equipment - see ambient conditions |
| ● EN 50125-3 | Yes; Signal and telecommunications systems - see ambient conditions; vibrations and shocks: Application point outside of tracks (1 m to 3 m away from track) |
| ● EN 50155 | Yes; Rail vehicles - temperature class OT4, ST1/ST2, horizontal mounting position |
| ● EN 61373 | Yes; Rail vehicles - vibrations and shocks: Category 1 Class A/B |
| ● Fire protection acc. to EN 45545-2 | Yes; For proof of conformity, see Service & Support |
| **Ambient conditions** | |
| Ambient temperature during operation | |
| ● horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| ● horizontal installation, max. | 70 °C; = Tmax; +85 °C for 10 min (OT4, ST1/ST2 acc. to EN 50155) |
| ● vertical installation, min. | -40 °C; = Tmin |


Subject to change without notice
© Copyright Siemens

| | |
|---|---|
| ● vertical installation, max. | 50 °C; = Tmax |
| Altitude during operation relating to sea level | |
| ● Installation altitude above sea level, max. | 2 000 m |
| ● Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) |
| Relative humidity | |
| ● With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on land craft, rail vehicles and special-purpose vehicles | |
| — to biologically active substances according to EN 60721-3-5 | Yes; Class 5B2 mold, fungus and dry rot spores (with the exception of fauna); Class 5B3 on request |
| — to chemically active substances according to EN 60721-3-5 | Yes; Class 5C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-5 | Yes; Class 5S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| ● Coatings for printed circuit board assemblies acc. to EN 61086 | Yes; Class 2 for high reliability |
| ● Protection against fouling acc. to EN 60664-3 | Yes; Type 1 protection |
| ● Electronic equipment on rolling stock acc. to EN 50155 | Yes; Class PC2 protective coating acc. to EN 50155:2017 |
| ● Military testing according to MIL-I-46058C, Amendment 7 | Yes; Discoloration of coating possible during service life |
| ● Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A |
| **Dimensions** | |
| Width | 20 mm |
| Height | 69.5 mm |
| Depth | 59 mm |
| **Weights** | |
| Weight, approx. | 46 g |
| **Other** | |
| Note: | for use in railway applications, also observe the product information "SIPLUS extreme RAIL" A5E37661960A, Online Support article 109736776 |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 14 | 27-24-26-92 |
| eClass | 12 | 27-24-26-92 |
| eClass | 9.1 | 27-24-26-92 |
| eClass | 9 | 27-24-26-92 |
| eClass | 8 | 27-24-26-92 |
| eClass | 7.1 | 27-24-26-92 |
| eClass | 6 | 27-24-26-92 |


© Copyright Siemens

| | | |
|---|---|---|
| ETIM | 10 | EC002584 |
| ETIM | 9 | EC002584 |
| ETIM | 8 | EC002584 |
| ETIM | 7 | EC002584 |
| IDEA | 4 | 3552 |
| UNSPSC | 15 | 32-15-17-03 |

## Approvals / Certificates

| General Product Approval | | | | | EMV |
|---|---|---|---|---|---|
| Manufacturer Declaration | UKCA | CE EG-Konf. | China RoHS | UL | RCM |

| Railway | Environment |
|---|---|
| Confirmation | EPD |

**last modified:** 7/16/2025


Subject to change without notice
© Copyright Siemens