SIEMENS

Data sheet 6AG2543-6WX00-4XE0

product type designation	**CP 1543SP-1 ISEC TX RAIL**
	SIPLUS ET 200SP CP 1543SP-1 ISEC TX rail based on 6GK7543-6WX00-0XE0 with conformal coating, -40…+70 °C, OT4 with ST1/2 (+85 °C for 10 minutes), security (firewall and VPN) open IE communication (TCP/IP, ISO-on-TCP, UDP) PG/OP, S7 routing, IP broadcast/multicast, SNMPV1/V3, DHCP, secure email, IPv4/IPv6, support of SINEMA Remote Connect with autoconfiguration, time synchronization via NTP, access to web server of CPU, BusAdapter required



Figure similar

Technical Product Detail Page	https://i.siemens.com/1P6AG2543-6WX00-4XE0
transfer rate	
transfer rate	
● at the 1st interface	10 ... 100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
● at the 1st interface / according to Industrial Ethernet	2
type of electrical connection	
● at the 1st interface / according to Industrial Ethernet	via ET 200SP bus adapter (RJ45, FC, SCRJ), integrated switch
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	19.2 ... 28.8 V
power loss [W]	6 W
ambient conditions	
ambient temperature	
● for vertical installation / during operation	-40 ... +50 °C
● for horizontally arranged busbars / during operation	-40 ... +70 °C
● during storage	-40 ... +70 °C
● during transport	-40 ... +70 °C
● note	+85 °C for 10 min (OT4, ST1/ST2 according to EN 50155)
installation altitude / at height above sea level / maximum	2000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
relative humidity	
● with condensation / according to IEC 60068-2-38 / maximum	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request
● conformity according to EN 60721-3-5	Yes; Class 5B2 mold and fungal spores (excluding fauna), Class 5B3 on request
resistance to chemically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation.

Subject to change without notice
© Copyright Siemens

● conformity according to EN 60721-3-5	Yes; Class 5C3 (RH < 75%) including salt spray acc. to EN 60068-2-52 (Severity level 3). The supplied plug covers must remain in place over the unused interfaces during operation!
resistance to mechanically active substances	
● conformity according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
● conformity according to EN 60721-3-5	Yes; Class 5S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation!
coating / for equipped printed circuit board / according to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of coating / for electronic devices in railway applications according to EN 50155	Yes; Protective coating of the Class PC2 according to EN 50155:2017
type of test / of the coating / according to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A	Yes; Conformal coating, class A
protection class IP	IP20
design, dimensions and weights	
width	60 mm
height	117 mm
depth	74 mm
net weight	0.18 kg
fastening method	
● 35 mm DIN-rail mounting	Yes
product features, product functions, product components / general	
number of units	
● per CPU / maximum	2
● note	2 CPs can be pluged in per CPU, simultaneous operation with BA Send and CM DP is possible
performance data / open communication	
number of possible connections / for open communication	
● by means of T blocks / maximum	32
data volume	
● as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum	65536 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
● maximum	16
● with OP connections / maximum	16
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	32
performance data / IT functions	
number of possible connections	
● as email client / maximum	1
product functions / management, configuration, engineering	
product function / MIB support	Yes
protocol / is supported	
● SNMP v1	Yes
● SNMP v3	Yes
● DCP	Yes
● LLDP	Yes
configuration software	
● required	STEP 7 Professional V14 (TIA Portal) or higher
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / diagnostics	
product function / web-based diagnostics	Yes; via ET 200SP CPU
product functions / security	

Subject to change without notice
© Copyright Siemens

firewall version	stateful inspection
product function / with VPN connection	IPsec, SINEMA RC
type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56
type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates
type of hashing algorithms / with VPN connection	MD5, SHA-1
number of possible connections / with VPN connection	4
product function	
● switch-off of non-required services	Yes
● blocking of communication via physical ports	Yes
● log file for unauthorized access	Yes
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	No
protocol / is supported	
● NTP	Yes
● NTP (secure)	Yes
time synchronization	
● from NTP-server	Yes
product functions / position detection	
certificate of suitability / railway application in accordance with EN 50121-3-2	Yes; EMC for railway vehicles
certificate of suitability / railway application in accordance with EN 50121-4	Yes; EMC for signaling and telecommunications equipment
certificate of suitability / railway application in accordance with EN 50124-1	Yes; Railway applications - Overvoltage category OV2 pollution degree PD2 rated impulse voltage UNi = 0.5 kVUNm = DC 24
certificate of suitability / railway application in accordance with EN 50125-1	Yes; Railway vehicles - See ambient conditions
certificate of suitability / railway application in accordance with EN 50125-2	Yes; Fixed-electrical installations - see ambient conditions
certificate of suitability / railway application in accordance with EN 50125-3	Yes; Signal and telecommunications equipment - see Ambient conditions vibrations and shocks: Application point outside the rails (distance 1 m to 3 m from rail)
certificate of suitability / railway application in accordance with EN 50155	Yes; Railway vehicles - temperature class OT4, ST1/ST2, horizontal mounting position
certificate of suitability / railway application in accordance with EN 61373	Yes; Railway vehicles - Vibrations and shocks Category 1 Class A/B
certificate of suitability / fire protection in accordance with EN 45545-2	Yes; Railway vehicles - for proof, see Service & Support
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under

© Copyright Siemens

https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval				EMV	Railway
Manufacturer Declaration	CE EG-Konf.	UKCA	China RoHS	RCM	Confirmation

last modified: 10/28/2025

Subject to change without notice
© Copyright Siemens