SIEMENS

Data sheet 6AV7860-1EX02-0AA1



SIMATIC Flat Panel accessory, USB-Link tranceiver, Use with Flat Panel extended with cabling sets >5m, Attention! Not suitable for PCU50 und PC627B/C

General information	
Product type designation	USB link transceiver, host unit
Installation type/mounting	
Wall mounting/direct mounting	Yes
Supply voltage	
Design of the power supply	via USB
Type of supply voltage	DC
Rated value (DC)	5 V
Power loss	
Power loss, typ.	0.5 W
Interfaces	
HMI-side interface	USB link (CAT5)
Device-side interface	USB 1.2
Ambient conditions	
Ambient temperature during operation	
● min.	5 °C
● max.	50 °C
Ambient temperature during storage/transportation	
● min.	-20 °C
● max.	60 °C
Weights	
Weight, approx.	3 kg
Scope of supply	
Delivery quantity in pieces	1
Classifications	

	Version	Classification
eClass	14	19-20-01-92
eClass	12	19-20-01-92
eClass	9.1	19-20-92-90
eClass	9	19-20-92-90
eClass	8	19-20-92-90
eClass	7.1	19-20-92-90
eClass	6	19-20-92-90
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Subject to change without notice
© Copyright Siemens

IDEA	4	6628
UNSPSC	15	43-21-16-12

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415
https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW

last modified: 3/12/2024

Subject to change without notice
© Copyright Siemens