SIEMENS

Data sheet 6AV7863-4MA16-2NA0

SIMATIC IFP2200 V2 PRO, 22″ multi-touch display (16:9) with 1920x1080 pixel resolution, PRO variant support arm, with operator control, for 24 V DC, DisplayPort, can be placed up to 100 m away HDBaseT, USB on the rear side, neutral design



Figure similar

General information	
Product type designation	IFP2200 V2 PRO
Short designation	Flat Panel 22" PRO multi-touch ext.
Display	
Design of display	TFT widescreen display, LED backlighting
Screen diagonal	21.5 in; 22"
Screen diagonal [cm]	54.6 cm
Display width	476.1 mm
Display height	267.8 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	178° x 178°
Resolution (pixels)	
● Image resolution	1 920 x 1 080
● Horizontal image resolution	1 920 pixel
● Vertical image resolution	1 080 pixel
● Pixel size, horizontal	0.248 mm
● Pixel size, vertical	0.248 mm
General features	
● Brightness/contrast	250 cd/m² / 1 000:1
● non-reflective and tempered mineral glass screen	Yes
● Detachable from computer unit	100 m; HDBaseT protocol
● Luminance	250 cd/m²
Backlighting	
● Type of backlighting	LED
● MTBF backlighting (at 25 °C)	30 000 h; At 25°C
● Backlight dimmable	Yes; 0-100 %
Control elements	
Control elements	multi-touch screen
Input device	
● Integrated mouse cursor control	Yes; Also externally via USB
Touch operation	
● Design as touch screen	Yes
● Design as multi-touch screen	Yes; Projective-capacitive
● Monitor keyboard	Yes
Installation type/mounting	
Design	Support arm mounting
Front mounting	No
Support arm mounting	Yes

Subject to change without notice
© Copyright Siemens

Stand mounting	No
VESA mounting	Yes; With VESA adapter set
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; PELV / SELV floating
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	1 A
Current consumption, max.	1.3 A
Starting current inrush I²t	0.5 A²·s
Power loss	
Power loss, typ.	24 W
Power loss, max.	31 W
Interfaces	
Number of USB interfaces	2; USB 2.0 type A
USB on the rear	Yes; 2x onboard
Connection for keyboard/mouse	USB
Video interfaces	
● DisplayPort	Yes; Display port V1.2
Touch interfaces	
● USB	Yes
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP65
NEMA (front)	
● Enclosure Type 4 at the front	Yes
● Enclosure Type 4x at the front	Yes
Standards, approvals, certificates	
Certificate of suitability	hazardous zone 2/22; shipbuilding
CE mark	Yes
UL approval	Yes
cULus	Yes; Corresponds to UL 508
FM approval	in preparation
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	Yes
EMC	CE, EN 55011, EN 61000-6-4, EN 61000-6-2
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	429.69596 kg
— global warming potential, (during production) [CO2 eq]	99.28 kg
— global warming potential, (during operation) [CO2 eq]	347.89539 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-20.11943 kg
Use in hazardous areas	
● ATEX Zone 2	Yes
● ATEX Zone 22	Yes
● IECEx Zone 2	Yes
● IECEx Zone 22	Yes
● FM Class I Division 2	No
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	45 °C
Ambient temperature during storage/transportation	
● min.	-20 °C

Subject to change without notice
© Copyright Siemens

● max.	60 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	3 500 m
Relative humidity	
● Operation, max.	95 %; no condensation
Vibrations	
● Vibration load in operation	1 gn
● Vibration load during transport/storage	1 gn
Shock testing	
● Shock load during operation	15 gn
● shock acceleration during storage/transport	15 gn
Mechanics/material	
Enclosure material (front)	With neutral design
● Aluminum	Yes
● Aluminum casting	Yes
● Glass	Yes; at front
Enclosure material (rear)	aluminum
Dimensions	
Width of the housing front	527 mm
Height of housing front	329 mm
Weights	
Weight (without packaging)	8.2 kg
Weight (with packaging)	9.1 kg

Classifications

	Version	Classification
eClass	14	19-20-02-01
eClass	12	19-20-02-01
eClass	9.1	19-20-02-01
eClass	9	19-20-02-01
eClass	8	19-20-02-01
eClass	7.1	19-20-02-01
eClass	6	19-20-02-01
ETIM	10	EC004862
ETIM	9	EC001428
ETIM	8	EC001428
ETIM	7	EC001428
IDEA	4	6675
UNSPSC	15	43-21-19-02

Approvals / Certificates

General Product Approval

Miscellaneous | Manufacturer Declaration









General Product Approval	EMV	For use in hazardous locations



BIS CRS








For use in hazardous locations	Maritime application	Environment

Subject to change without notice
© Copyright Siemens

Miscellaneous



NK / Nippon Kaiji Kyokai



last modified: 4/1/2025

Subject to change without notice
© Copyright Siemens