SIEMENS

Data sheet 6DL1193-6BH00-0SM0



Figure similar

SIMATIC ET 200SP HA, Carrier module in single carrier for holding one interface module of the ET 200SP HA incl. server module

General information	
Product type designation	IM carrier module, single
Product function	
● I&M data	Yes; Asset data
Supply voltage	
Rated value (DC)	24 V
Hardware configuration	
Slots	
● Number of slots	1
Potential separation	
between backplane bus and supply voltage	Yes
Isolation	
Isolation tested with	1 500 V DC/1 min, type test
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-40 °C
● horizontal installation, max.	70 °C
● vertical installation, min.	-40 °C
● vertical installation, max.	60 °C
Dimensions	
Width	100 mm
Height	204 mm
Depth	35 mm; measured without power plug
Weights	
Weight, approx.	250 g
Classifications	

	Version	Classification
eClass	14	27-24-26-07
eClass	12	27-24-26-07
eClass	9.1	27-24-26-07
eClass	9	27-24-26-07
eClass	8	27-24-26-07
eClass	7.1	27-24-26-07
eClass	6	27-24-26-07
ETIM	10	EC001603
ETIM	9	EC001603

Subject to change without notice
© Copyright Siemens

ETIM	8	EC001603
ETIM	7	EC001603

Approvals / Certificates

General Product Approval

EG-Konf. | Miscellaneous | UKCA | China RoHS | UL | KC

General Product Approval | For use in hazardous locations

RCM | EAC | IECEx | Declaration of Conformity | CCC | UL

For use in hazardous locations | Maritime application

ATEX | IECEx | Miscellaneous | ABS | Bureau Veritas | DNV

Maritime application | Environment

LRS | NK / Nippon Kaiji Kyokai | RINA | CCS (China Classification Society) | Siemens EcoTech | EPD

last modified: 10/23/2025

Subject to change without notice
© Copyright Siemens