SIEMENS

Data sheet 6ES7193-6AG70-0AA0



SIMATIC BusAdapter BA LC-LD/M12 1x LC-LD port, for single-mode fiber-optic cable, up to 20 km, 1x M12 socket, D-coded, PushPull

General information	
Product type designation	BA LC-LD / M12
Interfaces	
Number of PROFINET interfaces	1; 2 ports (switch) LC-LD / M12
Supports protocol for PROFINET IO	
● Number of LC ports	1; wavelength of 1 270 ... 1 380 nm, corresponds to 100BASE-LX
● Number of M12 ports	1
Cable length	
— Cu conductors	100 m
— single-mode fiber-optic cable 9/125 µm	20 km; 10 km for topology or IRT configuration; min. transmit power -15 dB, min. receiver sensitivity -28 dB
Standards, approvals, certificates	
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	27.1 kg
— global warming potential, (during production) [CO2 eq]	1.35 kg
— global warming potential, (during operation) [CO2 eq]	25.7 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.023 kg
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-30 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-30 °C
● vertical installation, max.	50 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual
Dimensions	
Width	20 mm
Height	69.5 mm
Depth	59 mm
Weights	
Weight, approx.	45 g
Classifications	

	Version	Classification
eClass	14	27-24-26-92

Subject to change without notice
© Copyright Siemens

eClass	12	27-24-26-92
eClass	9.1	27-24-26-92
eClass	9	27-24-26-92
eClass	8	27-24-26-92
eClass	7.1	27-24-26-92
eClass	6	27-24-26-92
ETIM	10	EC002584
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584

Approvals / Certificates

General Product Approval

EG-Konf. | UK CA | Manufacturer Declaration | UL | KC | RCM

For use in hazardous locations

UL | FM | CCC-Ex | ATEX | IECEx | Miscellaneous

For use in hazardous locations

Type Examination Certificate

Maritime application

ABS | BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai

Maritime application

RINA | RMRS | CCS (China Classification Society)

Environment

EPD

last modified: 9/19/2025

Subject to change without notice
© Copyright Siemens