SIEMENS

Data sheet 6ES7322-8BF00-0AB0



Figure similar

spare part SIMATIC S7-300, digital output SM 322, isolated, 8 DO, 24 V DC, 0.5 A (1x 8 DO), short-circuit protection diagnostics, 1x 20-pole

Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● permissible range, lower limit (DC)	20.4 V
● permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	90 mA
from backplane bus 5 V DC, max.	70 mA
Power loss	
Power loss, typ.	5 W
Digital outputs	
Number of digital outputs	8
Short-circuit protection	Yes; Electronic
● Response threshold, typ.	0.75 to 1.5 A
Limitation of inductive shutdown voltage to	L+ (-45 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
● on lamp load, max.	5 W
Load resistance range	
● lower limit	48 Ω
● upper limit	3 kΩ
Output voltage	
● for signal "1", min.	L+ (-0.8 to -1.6 V)
Output current	
● for signal "1" rated value	0.5 A
● for signal "1" permissible range for 0 to 40 °C, min.	10 mA
● for signal "1" permissible range for 0 to 40 °C, max.	0.6 A
● for signal "1" permissible range for 40 to 60 °C, min.	10 mA
● for signal "1" permissible range for 40 to 60 °C, max.	0.6 A
● for signal "1" minimum load current	10 mA
● for signal "0" residual current, max.	0.5 mA
Output delay with resistive load	
● "0" to "1", max.	180 µs
● "1" to "0", max.	245 µs
Parallel switching of two outputs	
● for uprating	No
● for redundant control of a load	Outputs with series diodes only
Switching frequency	
● with resistive load, max.	100 Hz

Subject to change without notice
© Copyright Siemens

● with inductive load, max.	2 Hz
● with inductive load (acc. to IEC 60947-5-1, DC13), max.	2 Hz
● on lamp load, max.	10 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	3 A
vertical installation	
— up to 40 °C, max.	4 A
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
● Diagnostic alarm	Yes; Parameterizable
Diagnoses	
● Diagnostic information readable	Yes
● Wire-break	Yes
● Short-circuit	Yes
● Fuse blown	No
● missing load voltage	Yes
Diagnostics indication LED	
● Rated load voltage PWR (green)	No
● Fuse OK FSG (green)	No
● Group error SF (red)	Yes
● Status indicator digital output (green)	Yes; per channel
● Channel fault indicator F (red)	Yes
Potential separation	
Potential separation digital outputs	
● between the channels, in groups of	8
● between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	500 V DC
connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	210 g
Classifications	

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Subject to change without notice
© Copyright Siemens

Approvals / Certificates

General Product Approval





Miscellaneous
Manufacturer Declaration




EMV







For use in hazardous locations



FM


For use in hazardous locations





Miscellaneous
CCC-Ex

Maritime application





Maritime application





NK / Nippon Kaiji Kyokai




CCS (China Classification Society)

last modified: 4/7/2025

Subject to change without notice
© Copyright Siemens