SIEMENS

Data sheet 6ES7332-7ND02-0AB0



Figure similar

spare part SIMATIC S7-300, analog output SM 332, isolated by channel, 4 AO, resolution 16 bit, 0-10 V, 1-5 V, +/-10 V, +/-20 mA, 0/4-20 mA, 20-pole, suitable for isochronous mode improved bus cycle times for the isochronous mode

Supply voltage	
Load voltage L+	
● Rated value (DC)	24 V
● Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	290 mA
from backplane bus 5 V DC, max.	120 mA
Power loss	
Power loss, typ.	3 W
Analog outputs	
Number of analog outputs	4; Isochronous mode
Voltage output, short-circuit protection	Yes
Voltage output, short-circuit current, max.	40 mA
Current output, no-load voltage, max.	18 V
Output ranges, voltage	
● 0 to 10 V	Yes
● 1 V to 5 V	Yes
● -10 V to +10 V	Yes
Output ranges, current	
● 0 to 20 mA	Yes
● -20 mA to +20 mA	Yes
● 4 mA to 20 mA	Yes
Load impedance (in rated range of output)	
● with voltage outputs, min.	1 kΩ
● with voltage outputs, capacitive load, max.	1 µF
● with current outputs, max.	500 Ω
● with current outputs, inductive load, max.	1 mH
Cable length	
● shielded, max.	200 m
Analog value generation for the outputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit
● Conversion time (per channel)	200 µs; in isochronous mode 640 µs
Settling time	
● for resistive load	0.2 ms
● for capacitive load	3.3 ms
● for inductive load	0.5 ms
Errors/accuracies	

Subject to change without notice
© Copyright Siemens

Operational error limit in overall temperature range	
● Voltage, relative to output range, (+/-)	0.12 %
● Current, relative to output range, (+/-)	0.18 %
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to output range, (+/-)	0.02 %
● Current, relative to output range, (+/-)	0.02 %
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
● Diagnostic alarm	Yes; Parameterizable
Diagnoses	
● Diagnostic information readable	Yes
Diagnostics indication LED	
● Group error SF (red)	Yes
Potential separation	
Potential separation analog outputs	
● between the channels	Yes
● between the channels and backplane bus	Yes
● between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	1 500 V DC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	117 mm
Weights	
Weight, approx.	220 g

Classifications

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous Confirmation

other	Environment

Subject to change without notice
© Copyright Siemens



Confirmation | Environmental Con-firmations | Environmental Con-firmations

last modified: 4/7/2025

Subject to change without notice
© Copyright Siemens