
SIEMENS

Data sheet 6ES7400-1JA11-0AA1



SIMATIC PCS 7, UR2 XTR S7-400 rack central and distributed with 9 slots, 2 redundant PS can be plugged in for extended temperature range and with conformal coating

General information	
Product type designation	UR2 XTR
Rack design	With Conformal Coating (ISA-S71.04 severity level G1; G2; G3) and operating temperature to 70 °C
Hardware configuration	
Rack	
● Communication bus	Yes
● P bus	Yes
Slots	
● Number of slots	9
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	70 °C
Ambient temperature during storage/transportation	
● min.	0 °C
● max.	70 °C
Mechanics/material	
rack profile material	aluminum
Dimensions	
Width	257.5 mm
Height	290 mm
Depth	27.5 mm
Weights	
Weight, approx.	1.5 kg
Classifications	

	Version	Classification
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03

Subject to change without notice
© Copyright Siemens

eClass	9	27-24-22-03
eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval



Manufacturer Declaration

Miscellaneous



China RoHS



General Product Approval	For use in hazardous locations





Declaration of Conformity





Type Examination Certificate

For use in hazardous locations	Maritime application











NK / Nippon Kaiji Kyokai

Maritime application	Environment



CCS (China Classification Society)



last modified: 6/7/2025

Subject to change without notice
© Copyright Siemens