SIEMENS

Data sheet 6ES7400-1TA11-0AA0

SIMATIC S7-400, rack UR1 Alu, central and distributed with 18 slots, 2 redundant PS can be plugged in



Figure similar

General information	
Product type designation	UR1
Hardware configuration	
Rack	
● Communication bus	Yes
● P bus	Yes
Slots	
● Number of slots	18
Standards, approvals, certificates	
CE mark	Yes
UKCA mark	Yes
UL approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	Yes
Ambient conditions	
Ambient temperature during operation	
● min.	0 °C
● max.	60 °C
Ambient temperature during storage/transportation	
● min.	0 °C
● max.	70 °C
Mechanics/material	
rack profile material	aluminum
Dimensions	
Width	482.5 mm
Height	290 mm
Depth	27.5 mm
Weights	
Weight, approx.	3 kg
Classifications	

	Version	Classification
eClass	14	27-24-22-03
eClass	12	27-24-22-03
eClass	9.1	27-24-22-03

Subject to change without notice
© Copyright Siemens

eClass	9	27-24-22-03
eClass	8	27-24-22-03
eClass	7.1	27-24-22-03
eClass	6	27-24-22-03
ETIM	10	EC000810
ETIM	9	EC000810
ETIM	8	EC000810
ETIM	7	EC000810
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates

General Product Approval

CE EG-Konf. | Manufacturer Declaration | Miscellaneous | UKCA | China RoHS | UL

General Product Approval | EMV | For use in hazardous locations

KC | RCM | RCM | RCM | IECEx | ATEX

For use in hazardous locations

Declaration of Conformity | FM | CCC | IECEx | Type Examination Certificate | ATEX

Maritime application

ABS | Bureau Veritas | DNV | Lloyd's Register LRS | NK / Nippon Kaiji Kyokai | PRS

Maritime application | Environment

RINA | CCS (China Classification Society) | EPD

last modified: 6/7/2025

Subject to change without notice
© Copyright Siemens