SIEMENS

## Data sheet 6ES7460-0AA01-0AB0



Figure similar

SIMATIC S7-400, interface module Send IM 460-0 for central coupling without PS transfer, with C-bus

| | |
|---|---|
| **Input current** | |
| from backplane bus 5 V DC, max. | 140 mA |
| **Power loss** | |
| Power loss, max. | 700 mW |
| **Hardware configuration** | |
| Cable length between first and last interface module, max. | 5 m |
| **Connection method** | |
| termination plug | 6ES7461-0AA0-7AA0 |
| **Dimensions** | |
| Width | 25 mm |
| Height | 290 mm |
| Depth | 280 mm |
| **Weights** | |
| Weight, approx. | 600 g |

**Classifications**

| | Version | Classification |
|---|---|---|
| eClass | 14 | 27-24-22-08 |
| eClass | 12 | 27-24-22-08 |
| eClass | 9.1 | 27-24-22-08 |
| eClass | 9 | 27-24-22-08 |
| eClass | 8 | 27-24-22-08 |
| eClass | 7.1 | 27-24-22-08 |
| eClass | 6 | 27-24-22-08 |
| ETIM | 10 | EC001423 |
| ETIM | 9 | EC001423 |
| ETIM | 8 | EC001423 |
| ETIM | 7 | EC001423 |
| IDEA | 4 | 3564 |
| UNSPSC | 15 | 32-15-17-05 |

**Approvals / Certificates**

**General Product Approval**


Subject to change without notice
© Copyright Siemens

Miscellaneous | China RoHS | KC

| General Product Approval | EMV | For use in hazardous locations |
|---|---|---|

FM

| For use in hazardous locations | Maritime application |
|---|---|

Type Examination Certificate

| Maritime application |
|---|

NK / Nippon Kaiji Kyokai

| Maritime application |
|---|

CCS (China Classification Society)

**last modified:** 6/7/2025


Subject to change without notice
© Copyright Siemens