SIEMENS

Data sheet 6ES7461-3AA01-0AA0



Figure similar

SIMATIC S7-400, interface module receiver IM 461-3 for distributed coupling up to 102 m, with C-bus

Input current	
from backplane bus 5 V DC, max.	620 mA
Power loss	
Power loss, max.	3 100 mW
Hardware configuration	
Cable length between first and last interface module, max.	102.25 m
Connection method	
termination plug	6ES7461-3AA0-7AA1
Dimensions	
Width	25 mm
Height	290 mm
Depth	280 mm
Weights	
Weight, approx.	620 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	10	EC001423
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Subject to change without notice
© Copyright Siemens

EG-Konf.	Miscellaneous	UKCA	China RoHS	UL	KC

General Product Approval	EMV		For use in hazardous locations		
RCM	RCM	RCM	IECEx	ATEX	FM

For use in hazardous locations				Maritime application	
CCC	IECEx	Type Examination Certificate	ATEX	ABS	BUREAU VERITAS

Maritime application					
DNV	LRS	NK / Nippon Kaiji Kyokai	PRS	RINA	RMRS

Maritime application
CCS (China Classification Society)

last modified: 6/7/2025

Subject to change without notice
© Copyright Siemens