SIEMENS

Data sheet 6ES7521-1BH50-0AA0

Siemens EcoTech

SIMATIC S7-1500, digital input module DI 16x24 V DC BA, sourcing input; 16 channels in groups of 16; Input delay 3.2 ms; Input type 3 (IEC 61131): Front connector (screw terminals or push-in) to be ordered separately



Figure similar

General information	
Product type designation	DI 16x24VDC SRC BA
HW functional status	FS01
Firmware version	V2.0.0
● FW update possible	Yes
Product function	
● I&M data	Yes; I&M0 to I&M3
● Isochronous mode	No
● Prioritized startup	Yes
Engineering with	
● STEP 7 TIA Portal configurable/integrated from version	V12 / V12
● STEP 7 configurable/integrated from version	V5.5 SP3 / -
● PROFIBUS from GSD version/GSD revision	V1.0 / V5.1
● PROFINET from GSD version/GSD revision	V2.3 / -
Operating mode	
● DI	Yes
● Counter	No
● MSI	Yes
Supply voltage	
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Power	
Power consumption from the backplane bus	0.9 W
Power loss	
Power loss, typ.	2.8 W
Digital inputs	
Number of digital inputs	16
Digital inputs, parameterizable	No
Source/sink input	Sourcing
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	-5 to +30V
● for signal "1"	-11 to -30V
Input current	
● for signal "1", typ.	4.5 mA

Subject to change without notice
© Copyright Siemens

Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	No
— at "0" to "1", min.	3 ms
— at "0" to "1", max.	4 ms
— at "1" to "0", min.	3 ms
— at "1" to "0", max.	4 ms
for interrupt inputs	
— parameterizable	No
for technological functions	
— parameterizable	No
Cable length	
● shielded, max.	1 000 m
● unshielded, max.	600 m
Encoder	
Connectable encoders	
● 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Alarms	
● Diagnostic alarm	No
● Hardware interrupt	No
Diagnoses	
● Monitoring the supply voltage	No
● Wire-break	No
● Short-circuit	No
Diagnostics indication LED	
● RUN LED	Yes; green LED
● ERROR LED	Yes; red LED
● Monitoring of the supply voltage (PWR-LED)	No
● Channel status display	Yes; green LED
● for channel diagnostics	No
● for module diagnostics	No
Potential separation	
Potential separation channels	
● between the channels	No
● between the channels, in groups of	16
● between the channels and backplane bus	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Siemens Eco Profile (SEP)	Siemens EcoTech
Suitable for safety functions	No
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	18.9 kg
— global warming potential, (during production) [CO2 eq]	12.1 kg
— global warming potential, (during operation) [CO2 eq]	7.66 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.02 kg
product functions / security / header	
signed firmware update	No
data integrity	No
Ambient conditions	
Ambient temperature during operation	
● horizontal installation, min.	-25 °C; From FS05
● horizontal installation, max.	60 °C

Subject to change without notice
© Copyright Siemens

● vertical installation, min.	-25 °C; From FS05
● vertical installation, max.	40 °C
Altitude during operation relating to sea level	
● Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	230 g

Classifications

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

Miscellaneous | EG-Konf. | UK CA | Manufacturer Declaration | UL | KC

General Product Approval | **For use in hazardous locations**

RCM | IECEx | FM | UL | FM | CCC-Ex

For use in hazardous locations | **Maritime application**

IECEx | ATEX | Type Examination Certificate | Miscellaneous | ABS | BUREAU VERITAS

Maritime application

DNV | LRS | NK / Nippon Kaiji Kyokai | RINA | RMRS | CCS (China Classification Society)

Maritime application | **Environment**

Subject to change without notice
© Copyright Siemens

last modified:	10/23/2025

Subject to change without notice
© Copyright Siemens