SIEMENS

Data sheet 6ES7923-3BF00-0HB0

cable D-SUB/end sleeve shielded 5m

connection cable shielded f. SIMATIC ET200 SP HA from 37-pole D-sub to bare ends w. wire end sleeve labeled 32 channels L = 5 m, 0.14mm2



Technical Product Detail Page	https://i.siemens.com/1P6ES7923-3BF00-0HB0
target system	SIMATIC ET 200SP HA
suitability for use	I/O modules
product type designation	Modular connection
product designation	Pre-assembled round cable
Operating data / header	
operating voltage / at DC	
● rated value	24 V
● maximum	60 V
ambient temperature	
● during operation	-25 ... +60 °C
● during storage	-30 ... +70 °C
General data / header	
suitability for interaction	
● input card PLC	Yes
● PLC output card	Yes
suitability for use	
● digital signal transmission	Yes
● analog signal transmission	Yes
Product properties, functions, components / general / header	
number of channels	32
design of cable	Round cable
wire length	5 m
number of poles	32
number of conductors / of connection cable	32
conductor cross section / rated value	0.14 mm²
color / of cable sheath	Black
outer diameter / of cable sheath	9 mm
material / of the connection cable sheath	PVC
design of the shield	braided shield
connector type	D-Sub connector
type of electrical connection / on enclosure	Female header
number of poles / at the 1st interface	37; control page
type of electrical connection / in the field	End sleeve
number of poles / at the 2nd interface	32; numbered
certificate of suitability	
● cULus approval	No
net weight	0.8 kg
last modified:	11/14/2025

Subject to change without notice
© Copyright Siemens

Subject to change without notice
© Copyright Siemens