SIEMENS

Data sheet for SINUMERIK ONE PPU 1740-1500

Article No. : **6FC5317-4AA00-1CA0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data

Input voltage	DC 24 V +20 % -15 %
Power consumption, max.	94 W

Mechanical data

Mounting position	Horizontal
Operator panel	Perpendicular
Net weight	6.10 kg (13.44 lb)
Width	398.0 mm (15.67 in)
Height	257.0 mm (10.12 in)
Depth	138.0 mm (5.43 in)

Degree of protection

Front side	IP65
Rear side	IP20 / UL open type

General tech. specifications

Mains buffering time	3 ms, 20 ms mit SITOP smart power supply

Ambient conditions

Ambient temperature

Operation on the front	0 ... 40 °C (32 ... 104 °F)
Operation at the rear	0 ... 45 °C (32 ... 113 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)
Transport	-20 ... 70 °C (-4 ... 158 °F)

Relative humidity

Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals

Certificate of suitability	CE, cULus, EAC, KC, RCM