SIEMENS

Data sheet for SINUMERIK 808D PPU 160.3

Article No. : **6FC5370-2BT03-0CA0**



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Input voltage	DC 24 V +20 % -15 %
Power consumption, max.	50 W

Mechanical data	
Mounting position	Vertical
Operator panel	Perpendicular
Net weight	2.90 kg (6.39 lb)
Width	265.0 mm (10.43 in)
Height	330.0 mm (12.99 in)
Depth	104.0 mm (4.09 in)
Degree of protection	
Front side	IP65 With the front flap closed
Rear side	IP20 / UL open type
Panel cutout	
Width	244.1 mm (9.61 in)
Height	307.1 mm (12.09 in)

General tech. specifications	
Mains buffering time	3 ms, 20 ms mit SITOP smart power supply

Ambient conditions	
Ambient temperature	
Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 50 °C (32 ... 122 °F)
Storage	-20 ... 60 °C (-4 ... 140 °F)
Transport	-20 ... 60 °C (-4 ... 140 °F)
Relative humidity	
Operation	5 ... 90 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals	
Certificate of suitability	CE, EAC, KC