SIEMENS

# Data sheet for SINUMERIK 808D PPU 150.3

## Article No. : 6FC5370-3BT03-0AA0



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

| Rated data | |
|---|---|
| Input voltage | DC 24 V +20 % -15 % |
| Power consumption, max. | 50 W |

| Mechanical data | |
|---|---|
| Mounting position | Vertical |
| Operator panel | Perpendicular |
| Net weight | 2.90 kg (6.39 lb) |
| Width | 265.0 mm (10.43 in) |
| Height | 330.0 mm (12.99 in) |
| Depth | 104.0 mm (4.09 in) |
| **Degree of protection** | |
| Front side | IP65 With the front flap closed |
| Rear side | IP20 / UL open type |
| **Panel cutout** | |
| Width | 244.1 mm (9.61 in) |
| Height | 307.1 mm (12.09 in) |

| General tech. specifications | |
|---|---|
| Mains buffering time | 3 ms, 20 ms mit SITOP smart power supply |

| Ambient conditions | |
|---|---|
| **Ambient temperature** | |
| Operation on the front | 0 ... 45 °C (32 ... 113 °F) |
| Operation at the rear | 0 ... 50 °C (32 ... 122 °F) |
| Storage | -20 ... 60 °C (-4 ... 140 °F) |
| Transport | -20 ... 60 °C (-4 ... 140 °F) |
| **Relative humidity** | |
| Operation | 5 ... 90 % |
| Storage | 5 ... 95 % |
| Transport | 5 ... 95 % |

| Approvals | |
|---|---|
| Certificate of suitability | CE, EAC, KC |