SIEMENS

Data sheet 6GK5334-2TS01-4AR3

SCALANCE XRM334; managed layer 2; IE switch, 19" rack; 24x 100/1000 Mbps RJ45 port; 2x 1G/2.5G/5G/10 Gbps RJ45 8x 1G/10G SFP+ port; LED diagnostics; error signaling contact; select/set button; PROFINET IO device; network management; integrated redundancy manager; office features (RSTP, VLAN, IGMP,..); CLP included in scope of supply; power supply 2x230 V AC;



product type designation	
product brand name	SCALANCE
product type designation	XRM334
Technical Product Detail Page	https://i.siemens.com/1P6GK5334-2TS01-4AR3
transfer rate	
transfer rate	10, 100, 1000 Mbit/s
transfer rate	2.5, 5, 10 Gbit/s
interfaces / for communication / integrated	
number of electrical connections	
● for network components or terminal equipment	26; RJ45
number of 10/100/1000 Mbit/s RJ45 ports	
● with securing collar	26
number of 1000/2500/5000/10000 Mbps RJ45 ports / with securing collar	2
number of electrical connections	
● for SFP+	8; 1000 Mbps and 10000 Mbps SFP usable
interfaces / other	
number of electrical connections	
● for operator console	1
● for signaling contact	1
● for power supply	2
design of the removable storage	
● CLP	Yes
operating voltage / of the signaling contacts	
● at AC / rated value	24 V
● at DC / rated value	24 V
operational current / of the signaling contacts	
● at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage supply / redundant power supply unit	Yes
type of voltage / 1 / of the supply voltage	
● supply voltage / 1 / rated value	100V ... 250V DC
● power loss [W] / 1 / rated value	99 W
● supply voltage / 1 / voltage range	77 ... 300
● consumed current / 1 / maximum	0.8 A
● product component / 1 / fusing at power supply input	Yes
type of voltage / 2 / of the supply voltage	
● supply voltage / 2 / rated value	240 V; 110V ... 240V AC

Subject to change without notice
© Copyright Siemens

● power loss [W] / 2 / rated value	99 W
● supply voltage / 2 / voltage range	85 ... 264
● consumed current / 2 / maximum	0.8 A
ambient conditions	
ambient temperature / in horizontal mounting position / during operation	-25 ... +60 °C; Starting at -25 °C; The maximum ambient temperature during operation depends on the operating height and the plug-in transceivers, see also manual.
installation altitude / at height above sea level / maximum	3000 m
relative humidity	
● at 25 °C / without condensation / during operation / maximum	95 %
operating condition / fanless operation	Yes
protection class IP	IP20
design, dimensions and weights	
design	19-inch rack
number of modular height units / relating to 19-inch cabinet	1
width	446 mm
height	43.6 mm
depth	374.8 mm
net weight	8.4 kg
material / of the enclosure	metal
fastening method	
● 19-inch installation	Yes
product features, product functions, product components / general	
cascading in cases of star topology	any (depending only on signal propagation time)
number of automatically learnable MAC addresses	16382
number of QoS queues / per port	8
product function	
● QoS according to IEEE 802.1Q	Yes
product feature	
● Store & Forward switching method	Yes
product license	
product license / Upgrade license	Yes; layer 3 license
product functions / management, configuration, engineering	
product function	
● CLI	Yes
● web-based management	Yes
● MIB support	Yes
● TRAPs via email	Yes
● configuration with STEP 7	Yes
● RMON	No
● SMTP server	No
● port mirroring	Yes
● multiport mirroring	Yes
● Encapsulated Remote Traffic Mirroring (ERTM)	Yes
● CoS	Yes
● PROFINET IO diagnosis	Yes
● switch-managed	Yes
PROFINET conformity class	B
network load class / according to PROFINET	II
telegram length / for Ethernet / maximum	9194 byte
protocol / is supported	
● Telnet	No
● HTTP	Yes
● HTTPS	Yes
● TFTP	Yes
● FTP	Yes
● SFTP	Yes
● BOOTP	Yes

© Copyright Siemens

● NETCONF	Yes
● GMRP	Yes
● DCP	Yes
● LLDP	Yes
● EtherNet/IP	Yes
● SNMP v1	Yes
● SNMP v2	Yes
● SNMP v3	Yes
● IGMP (snooping/querier)	Yes
identification & maintenance function	
● I&M0 - device-specific information	Yes
● I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function	
● port diagnostics	Yes
● statistics Packet Size	Yes
● statistics packet type	Yes
● error statistics	Yes
● SysLog	Yes
product functions / VLAN	
product function	
● VLAN - port based	Yes
● VLAN - protocol-based	No
● VLAN - IP-based	No
● VLAN dynamic	Yes
number of VLANs / maximum	512
number of VLANs - dynamic / maximum	512
product functions / DHCP	
product function	
● DHCP server	No
● DHCP client	Yes
● DHCP Option 82	No
● DHCP Option 66	Yes
● DHCP Option 67	Yes
product functions / redundancy	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes
product function	
● media redundancy protocol (MRP) with redundancy manager	Yes
● Media Redundancy Protocol Interconnection (MRP-I)	No
● ring redundancy	Yes
● high speed redundancy protocol (HRP) with redundancy manager	No
● high speed redundancy protocol (HRP) with standby redundancy	No
● redundancy procedure STP	Yes
● redundancy procedure RSTP	Yes
● redundancy procedure RSTP+	Yes
● redundancy procedure MSTP	Yes
● passive listening	No
● eRSTP	Yes
protocol / is supported	
● LACP	No
system modification during operation	
product function / configuration in RUN via CiR/H-CiR	No
product functions / security	
product conformity / according to IEEE 802.1x-port based Network Access Control	No
protocol / is supported	
● RADIUS	Yes

Subject to change without notice
© Copyright Siemens

● SSH	Yes
● SSL	Yes
product functions / time	
product function	
● SICLOCK support	Yes
● NTP-client	Yes
● IEEE 1588 v2 transparent forwarding	Yes
protocol / is supported	
● NTP	Yes
● SNTP	Yes
● IEEE 1588 profile default	Yes
accuracy / at IEEE 1588 v2	
● not less than	100 µs
● typical	50 ns
standards, specifications, approvals	
certificate of suitability	
● CE marking	Yes
● UKCA marking	Yes
● cULus approval	Yes
● KC approval	Yes
● Regulatory Compliance Mark (RCM)	Yes
product conformity / according to EMC-guideline	2014/30/EU
standard	
● for EMC interference emission	EN 61000-6-4
● for immunity to EMC	EN 61000-6-2
standards, specifications, approvals / other	
certificate of suitability	
● railway application in accordance with EN 50121-4	Yes; use only in areas not accessible to the public
● railway application in accordance with EN 50125-3	Yes; Section 4.2: Class AX (up to 2000m); section 4.3: T1: Containers N.T.C and T.C. / Buildings N.C.C and C.C, T2: Containers N.T.C and T.C. / Buildings N.C.C and C.C, TX: Containers N.T.C and T.C. / Buildings N.C.C and C.C., derating according to the manual must be observed when SFP/SFP+ transceivers are used; section 4.4: T1: Containers C.C. / Buildings N.C.C and C.C., T2: Containers C.C. / Buildings N.C.C and C.C, T3: Containers C.C. / Buildings N.C.C and C.C; section 4.11: C1: Indoor, C2: Indoor (except condensation), C3: Indoor (except condensation), 4B1, 4S10, UL 62368-1, UL 61010-2-10; section 4.13: partially, Test Fc: Vibration EN 60068-2-6; IEC 60068-2-6, Test Ea: Shock EN 60068-2-27; IEC 60068-2-27, Test Ec: Rough handling, shocks EN 60068-2-31; IEC 60068-2-31; section 4.14: yes; section 4.15: yes, according to manual.
● RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
IT security for industrial automation systems / according to IEC 62443-4-2:2019	Yes
standards, specifications, approvals / marine classification	
Marine classification association	
● American Bureau of Shipping Europe Ltd. (ABS)	No
● French marine classification society (BV)	No
● Chinese Classification Society (CCS)	No
● Det Norske Veritas (DNV)	No
● Korean Register of Shipping (KRS)	No
● Lloyds Register of Shipping (LRS)	No
● Nippon Kaiji Kyokai (NK)	No
● Polski Rejestr Statkow (PRS)	No
● Royal Institution of Naval Architects (RINA)	No
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	1122.93 kg
● during manufacturing	207 kg
● during operation	915 kg

© Copyright Siemens

● after end of life	0.93 kg
product functions / general	
MTBF	10.6 a
reference temperature / for MTBF determination	40 °C
warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval





China RoHS




General Product Approval	Radio Equipment Type Approval Certificate	Test Certificates	Environment	Industrial Communication
TUEV	KC	Type Test Certificates/Test Report	EPD	PROFINET

last modified: 10/30/2025

Subject to change without notice
© Copyright Siemens