SIEMENS

Data sheet 6GK5992-4SA00-8AA0

product type designation	**MM992-4CU**
	SCALANCE X accessory; Media module MM992-4CU; 4x 1000 Mbit/s RJ45 ports, electrical; without securing collar.



Technical Product Detail Page	https://i.siemens.com/1P6GK5992-4SA00-8AA0
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of electrical connections	
● for network components or terminal equipment / maximum	4
number of 10/100/1000 Mbit/s RJ45 ports	4
type of electrical connection	
● for network components or terminal equipment	RJ45
ambient conditions	
ambient temperature	
● during operation	0 ... 60 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	Media module
width	120.3 mm
height	22.3 mm
depth	275.5 mm
net weight	0.3 kg
fastening method	latched
● installation in media module slot	Yes
standards, specifications, approvals	
standard	
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
● for emitted interference	EN 61000-6-4 (Class A)
● for interference immunity	EN 61000-6-2
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
● CE marking	Yes
● C-Tick	Yes
● KC approval	Yes
● CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
● CCC / for hazardous zone according to GB standard / as marking	Ex nA IIC T4 Gc
● E1 approval	No

Subject to change without notice
© Copyright Siemens

Marine classification association	
● French marine classification society (BV)	Yes

standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	102.1 kg
● during manufacturing	10.1 kg
● during operation	91.9 kg
● after end of life	0.1 kg

further information / internet links	
internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval

CE EG-Konf. | Declaration of Conformity | CCC | EAC | China RoHS | RCM

EMV	For use in hazardous locations			Maritime application
KC	ATEX	IECEx	FM	CCC-Ex	ABS

Maritime application

BUREAU VERITAS | DNV | LRS | NK / Nippon Kaiji Kyokai | PRS | RINA

Environment

© Copyright Siemens

last modified:	11/14/2025

Subject to change without notice
© Copyright Siemens