SIEMENS

Data sheet 6GK6000-8CG02-2EA1

product type designation	**RUGGEDCOM 2488-22CG02 Module CC**
	Media Module for RUGGEDCOM RSG 2488, 2 x FastConnect RJ45, 10 /100/1000BASE-TX



Technical Product Detail Page	https://i.siemens.com/1P6GK6000-8CG02-2EA1
suitability for operation	RSG2488
interfaces	
number of electrical/optical connections / for network components or terminal equipment / maximum	2
number of electrical connections	
● for network components or terminal equipment / maximum	2
number of 10/100/1000 Mbit/s RJ45 ports	2
type of electrical connection	
● for network components or terminal equipment	RJ45
ambient conditions	
ambient temperature	
● during operation	-40 ... +85 °C
● during storage	-40 ... +85 °C
● during transport	-40 ... +85 °C
● note	A maximum operating temperature of +85 °C is permissible for a duration of 16 hours
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP40 (when installed)
design, dimensions and weights	
design	Media module
width	50 mm
height	22 mm
depth	91 mm
net weight	0.22 kg
product feature / conformal coating	Yes
fastening method	screwed
● installation in media module slot	Yes
standards, specifications, approvals	
standard	
● for EMC	FCC Part 15 (Class A), EN55022 (CISPR22 Class A)
● for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
● for hazardous zone / from CSA and UL	Hazardous Locations: Class 1 Division 2
● for emitted interference	EN 61000-6-4 (Class A)
● for interference immunity	EN 61000-6-2
laser protection class	21 CFR Chapter 1, Subchapter J
certificate of suitability	EN 61000-6-2, EN 61000-6-10

Subject to change without notice
© Copyright Siemens

● CE marking	Yes
● C-Tick	No
● KC approval	No
● E1 approval	No
● IEC 61850-3	Yes

further information / internet links

internet link	
● to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
● to website: Industry Mall/RUGGEDCOM selector	https://www.siemens.com/ruggedcom-selector
● to website: Industrial communication	https://www.siemens.com/simatic-net
● to website: Siemens RUGGEDCOM	https://www.siemens.com/ruggedcom
● to web page: SiePortal	https://sieportal.siemens.com/
● to website: Image database	https://www.automation.siemens.com/bilddb
● to website: CAx-Download-Manager	https://www.siemens.com/cax
● to website: Industry Online Support	https://support.industry.siemens.com

security information

security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates

General Product Approval	other
Manufacturer Declaration	inspection certificate

last modified: 11/14/2025

Subject to change without notice
© Copyright Siemens